

ZYXEL

Zyxel GS2220-10-EU0101F netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Zwart

Merk : Zyxel

Artikelcode: GS2220-10-EU0101F

Productnaam : GS2220-10-EU0101F



Zyxel GS2220-10-EU0101F. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 10. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 20 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack-montage

| Beheerfuncties                                  |                                                                                                                                                                             | Design                                 |                                               |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|-----------------------------------------------|
| Switch type *                                   | Managed                                                                                                                                                                     | Rack-montage *                         | ✓                                             |
| Switch-laag                                     | L2                                                                                                                                                                          | Kleur van het product                  | Zwart                                         |
| Quality of Service (QoS)                        | ✓                                                                                                                                                                           | Certificering                          | LVD, BSMI FCC 15 A, CE EMC A, BSMI ENC RoHS A |
| Web-gebaseerd management                        | ✓                                                                                                                                                                           | Prestatie                              |                                               |
| Locatie-instellingen (CLI) configureren         | ✓                                                                                                                                                                           | Intern geheugen                        | 256 MB                                        |
| System event log                                | ✓                                                                                                                                                                           | Flash memory                           | 32 MB                                         |
| Poorten & interfaces                            |                                                                                                                                                                             | Upgraden van firmware mogelijk         | ✓                                             |
| Aantal basis-switching RJ-45 Ethernet-poorten * | 10                                                                                                                                                                          | Fanloos                                | ✓                                             |
| Type basis-switching RJ-45 Ethernet-poorten *   | Gigabit Ethernet (10/100/1000)                                                                                                                                              | Mean time between failures (MTBF)      | 1213492 uur                                   |
| Netwerk                                         |                                                                                                                                                                             | Energie                                |                                               |
| Netwerkstandaard *                              | IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | AC-ingangsspanning                     | 100 - 240 V                                   |
|                                                 |                                                                                                                                                                             | AC-ingangsfrequentie                   | 50 - 60 Hz                                    |
| 10G support *                                   | ✗                                                                                                                                                                           | Vermogensverbruik (max)                | 11 W                                          |
| Koperen ethernetbekabelingstechnologie          | 10BASE-TX, 1000BASE-T                                                                                                                                                       | Power over Ethernet (PoE)              |                                               |
| Datastroombeheer                                | ✓                                                                                                                                                                           | Power over Ethernet (PoE) *            | ✗                                             |
| Verbindingsaggregatie                           | ✓                                                                                                                                                                           | Eisen aan de omgeving                  |                                               |
| Broadcast stormbeheer                           | ✓                                                                                                                                                                           | Bedrijfstemperatuur (T-T)              | 0 - 50 °C                                     |
| Rate limiting                                   | ✓                                                                                                                                                                           | Temperatuur bij opslag                 | -40 - 70 °C                                   |
| Spanning tree protocol                          | ✓                                                                                                                                                                           | Relatieve vochtigheid in bedrijf (V-V) | 10 - 95 procent                               |
| VLAN=ondersteuning                              | ✓                                                                                                                                                                           | Luchtvochtigheid bij opslag            | 10 - 95 procent                               |
| Virtuele LAN-functies                           | Port-based VLAN, Private VLAN, Protocol-based VLAN, Voice VLAN                                                                                                              | Warmtedissipatie                       | 37,51 BTU/h                                   |
| Data-uitwisseling                               |                                                                                                                                                                             | Gewicht en omvang                      |                                               |
| Switchingcapaciteit *                           | 20 Gbit/s                                                                                                                                                                   | Breedte                                | 267 mm                                        |
| Verzending snelheid                             | 15 Mpps                                                                                                                                                                     | Diepte                                 | 162 mm                                        |
| MAC-adrestabel *                                | 16000 entries                                                                                                                                                               | Hoogte                                 | 44 mm                                         |
|                                                 |                                                                                                                                                                             | Gewicht                                | 1,3 kg                                        |
|                                                 |                                                                                                                                                                             | Verpakking                             |                                               |
|                                                 |                                                                                                                                                                             | Meegeleverde kabels                    | AC                                            |

| Data-uitwisseling                   |                                                                     | Verpakking                                |         |
|-------------------------------------|---------------------------------------------------------------------|-------------------------------------------|---------|
| Packet buffergeheugen               | 1,5 MB                                                              | Breedte verpakking                        | 375 mm  |
| Beveiliging                         |                                                                     | Diepte verpakking                         | 235 mm  |
| DHCP-functies                       | DHCP client, DHCP relay, DHCP snooping, DHCPv6 client, DHCPv6 relay | Hoogte verpakking                         | 61 mm   |
|                                     |                                                                     | Gewicht verpakking                        | 2,21 kg |
| Logistieke gegevens                 |                                                                     |                                           |         |
| Access Control List (ACL)           | ✓                                                                   | Code geharmoniseerd systeem (HS) 85176990 |         |
| IGMP snooping                       | ✓                                                                   |                                           |         |
| Ondersteunde beveiligingsalgoritmen | SNMP, SNMPv2, SNMPv3, SSH-2, SSL/TLS                                |                                           |         |
| MAC adres filtering                 | ✓                                                                   |                                           |         |
| Authenticatie                       | Gast-VLAN, MAC-gebaseerde authenticatie                             |                                           |         |
| Authenticatie type                  | IEEE 802.1x, RADIUS                                                 |                                           |         |
| Multicast-functies                  |                                                                     |                                           |         |
| Multicast-ondersteuning             | ✓                                                                   |                                           |         |



4718937607365

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date