TP-Link Tapo C310 kubus IP-beveiligingscamera Buiten 2304 x 1296 Pixels Muur

Merk : TP-Link

Productfamilie: Tapo

Artikelcode: TAPO C310

Productnaam : C310

TP-Link Tapo C310. Soort: IP-beveiligingscamera, Ondersteuning voor plaatsing: Buiten, Connectiviteitstechnologie: Bedraad en draadloos. Montagewijze: Muur, Kleur van het product: Wit, Vormfactor: kubus. Field of view (FOV) hoek: 104°. Omvang optische sensor: 25,4 / 2,7 mm (1 / 2.7"). Vaste focale lengte: 3,89 mm



Performance		Network	
Type * Placement supported *	IP security camera Outdoor Wired & Wireless	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
		Bluetooth *	×
Connectivity technology *		Storage	
Day/night mode Certification	CE, NCC	Built-in HDD *	×
Design	-,	Card reader integrated	✓
Form factor *	Cube	Compatible memory cards Maximum memory card size	MicroSD (TransFlash) 128 GB
Mounting type *	Wall	Ports & interfaces	120 00
Product colour *	White	Ethernet LAN (RI-45) ports	1
LED indicators Protection features	System Dust resistant, Rain proof	DC-in jack	·
International Protection (IP) code	IP66	Security	
Weatherproof	✓	Video motion detection	1
Camera		Security algorithms	128-bit AES, SSL/TLS, WPA, WPA2-
Camera pan control	×	Security algorithms	PSK
Camera tilt control	×	Management features	
Field of view (FOV) angle	104°	Reset button	✓
Image sensor		Power	
Noushau of assesses			10 DC
Number of sensors	1	Power source type *	AC, DC
Optical sensor size	1 25.4 / 2.7 mm (1 / 2.7")	AC input voltage	100 - 240 V
		AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
Optical sensor size Lens system Number of lenses *	25.4 / 2.7 mm (1 / 2.7") 1	AC input voltage	100 - 240 V
Optical sensor size Lens system	25.4 / 2.7 mm (1 / 2.7")	AC input voltage AC input frequency DC output voltage	100 - 240 V 50 - 60 Hz 9
Optical sensor size Lens system Number of lenses * Maximum aperture number	25.4 / 2.7 mm (1 / 2.7") 1 2.2	AC input voltage AC input frequency DC output voltage DC output current	100 - 240 V 50 - 60 Hz 9
Optical sensor size Lens system Number of lenses * Maximum aperture number Fixed focal length	25.4 / 2.7 mm (1 / 2.7") 1 2.2	AC input voltage AC input frequency DC output voltage DC output current Operational conditions Operating temperature (T-T) Storage temperature (T-T)	100 - 240 V 50 - 60 Hz 9 0.6 A 0 - 40 °C -40 - 70 °C
Optical sensor size Lens system Number of lenses * Maximum aperture number Fixed focal length Night vision	25.4 / 2.7 mm (1 / 2.7") 1 2.2 3.89 mm	AC input voltage AC input frequency DC output voltage DC output current Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	100 - 240 V 50 - 60 Hz 9 0.6 A 0 - 40 °C -40 - 70 °C 10 - 90%
Optical sensor size Lens system Number of lenses * Maximum aperture number Fixed focal length Night vision Night vision *	25.4 / 2.7 mm (1 / 2.7") 1 2.2 3.89 mm	AC input voltage AC input frequency DC output voltage DC output current Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	100 - 240 V 50 - 60 Hz 9 0.6 A 0 - 40 °C -40 - 70 °C
Optical sensor size Lens system Number of lenses * Maximum aperture number Fixed focal length Night vision Night vision * Night vision distance	25.4 / 2.7 mm (1 / 2.7") 1 2.2 3.89 mm ✓ 30 m	AC input voltage AC input frequency DC output voltage DC output current Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	100 - 240 V 50 - 60 Hz 9 0.6 A 0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%
Optical sensor size Lens system Number of lenses * Maximum aperture number Fixed focal length Night vision Night vision * Night vision distance LED type Infra-red wavelength Video Maximum resolution * Total megapixels * Video formats supported	25.4 / 2.7 mm (1 / 2.7") 1 2.2 3.89 mm ✓ 30 m IR 850 nm Z304 × 1296 pixels 3 MP H.264	AC input voltage AC input frequency DC output voltage DC output current Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	100 - 240 V 50 - 60 Hz 9 0.6 A 0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90% Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1 Android 7.0,
Optical sensor size Lens system Number of lenses * Maximum aperture number Fixed focal length Night vision Night vision * Night vision distance LED type Infra-red wavelength Video Maximum resolution * Total megapixels *	25.4 / 2.7 mm (1 / 2.7") 1 2.2 3.89 mm ✓ 30 m IR 850 nm ✓ 2304 x 1296 pixels 3 MP	AC input voltage AC input frequency DC output voltage DC output current Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) System requirements	100 - 240 V 50 - 60 Hz 9 0.6 A 0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90% Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 9.0,


Audio		Weight & dimensions	
Built-in speaker(s) Audio system	✔ 2-way	Depth Height	103.4 mm 64.3 mm
Built-in microphone	✓	Packaging data	
Network		Package width	189.5 mm
Ethernet LAN *	× IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Package depth Package height	201.5 mm 92.5 mm
Networking standards		Package weight	420 g
Wi-Fi *	1	Packaging content	
		Number of cameras *	1
		Logistics data	

Harmonized System (HS) code

85258900







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.