



TP-Link TL-SL1218P netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Zwart

Merk : TP-Link

Artikelcode: TL-SL1218P

Productnaam : TL-SL1218P



TP-Link TL-SL1218P. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 18. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 7,2 Gbit/s. Netwerkstandaard: IEEE 802.3af, IEEE 802.3at, IEEE 802.3x. Power over Ethernet (PoE). Rack-montage, Vormfactor: 1U



Beheerfuncties		Energie	
Switch type *	Unmanaged	AC-ingangsspanning	100 - 240 V
Traffic-classificatie	✓	AC-ingangsfrequentie	50 - 60 Hz
Poorten & interfaces		Vermogensverbruik (max)	172,8 W
Aantal basis-switching RJ-45 Ethernet-poorten *	18	Power over Ethernet (PoE)	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) *	✓
Fast Ethernet (koperen) ports kwantiteit	16	Aantal Power over Ethernet plus (PoE +)-poorten	16
Aantal Gigabit Ethernet (koper)-poorten	2	Vermogen per poort Power over Ethernet (PoE)	30 W
Aantal Combo SFP-poorten	1	Totaal Power over Ethernet (PoE)-budget	150 W
Netwerk		Eisen aan de omgeving	
Netwerkstandaard *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3x	Bedrijfstemperatuur (T-T)	0 - 50 °C
10G support *	✗	Temperatuur bij opslag	-40 - 70 °C
Ondersteundende kabel types	Cat3, Cat4, Cat5, Cat5e, Cat6	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Auto MDI/MDI-X	✓	Luchtvochtigheid bij opslag	5 - 90 procent
Auto-negotiation	✓	Warmtedissipatie	589,25 BTU/h
Data-uitwisseling		Gewicht en omvang	
Switchingcapaciteit *	7,2 Gbit/s	Breedte	440 mm
Verzending snelheid	5,36 Mpps	Diepte	180 mm
MAC-adrestabel *	8000 entries	Hoogte	44 mm
Jumbo Frames ondersteuning	✓	Inhoud van de verpakking	
Jumbo frames	10000	Meegeleverde kabels	AC
Packet buffergeheugen	4,1 MB	Snelstartgids	✓
Design		Verpakking	
		Breedte verpakking	250 mm

Design		Verpakking	
Rack-montage *	✓	Diepte verpakking	528 mm
Vormfactor	1U	Hoogte verpakking	80 mm
Kleur van het product	Zwart	Gewicht verpakking	2,8 kg
Materiaal behuizing	Metaal	Certificaten	
LED-indicatoren	✓	Certificering	CE, FCC, RoHS
Aantal ventilatoren	2 ventilator(en)	Logistieke gegevens	
Energie		Code geharmoniseerd systeem (HS) 85176990	
Stroombron *	AC		
Vermogenstoevoer inclusief *	✓		



6935364052812



6935364052829



0845973088712



845973088712



5715063228371

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.