



## ACT Blauwe 1 meter U/UTP CAT6 patchkabel snagless met RJ45 connectoren

**Merk :** ACT

**Artikelcode:** IS8601

**Productnaam :** Blauwe 1 meter U/UTP CAT6 patchkabel snagless met RJ45 connectoren



- Volledig koperen 24AWG geleiders en 50µ vergulde RJ-45 contacten.
  - Voldoen aan de internationale normen
  - Kabels zijn 100% getest.
- Blauwe 1m U/UTP CAT6 patchkabel snagless met RJ45 connectoren

**ACT Blauwe 1 meter U/UTP CAT6 patchkabel snagless met RJ45 connectoren:**

ACT patchkabels worden voorzien van puur koperen geleiders en voldoen volledig aan de normen die in de ANSI/TIA-568-C2 beschreven staan. De combinatie van professioneel geïnstalleerde, gestructureerde bekabeling, betrouwbare actieve apparatuur en koperen patchkabels, zorgen voor een stabiel functionerend netwerk waar u geen omkijken naar heeft. Door materialen in uw netwerk toe te passen, die conform de standaard geproduceerd zijn, zal uw actieve apparatuur probleemloos en optimaal presteren.

Voor PoE (Power over Ethernet) toepassingen is het van belang om patchkabels met koperen geleiders te gebruiken. Alle ACT patchkabels hebben koperen geleiders en zijn uitermate geschikt voor toepassingen in netwerken waar PoE toegepast wordt.

Compatible met CPR Euroclass: ECA



| Kenmerken                  |             | Kenmerken                                 |                          |
|----------------------------|-------------|-------------------------------------------|--------------------------|
| Kleur van het product *    | Blauw       | Materiaal buitenmantel                    | Polyvinyl chloride (PVC) |
| Snoerlengte *              | 1 m         | Geleidermateriaal                         | Koper                    |
| Kabel standaard *          | Cat6        | AWG draad omvang                          | 24                       |
| Kabelafscherming *         | U/UTP (UTP) | Frequentie                                | 250 MHz                  |
| Aansluiting 1 *            | RJ-45       | <b>Eisen aan de omgeving</b>              |                          |
| Aansluiting 2 *            | RJ-45       | Bedrijfstemperatuur (T-T)                 | -20 - 60 °C              |
| Aansluiting 1 type *       | Mannelijk   | <b>Logistieke gegevens</b>                |                          |
| Aansluiting 2 type *       | Mannelijk   | Code geharmoniseerd systeem (HS) 84733080 |                          |
| Contact geleider materiaal | Goud        |                                           |                          |



8716065254617

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date