

TP-Link TL-SF1016D Unmanaged Fast Ethernet (10/100) Zwart

Merk : TP-Link

Artikelcode: TL-SF1016D V7

Productnaam : TL-SF1016D

TP-Link TL-SF1016D. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 3,2 Gbit/s. Netwerkstandaard: IEEE 802.3u, IEEE 802.3x. DC voltage input: 9 V. Netstekker: DC-in ingang. Ophangstelsysteem voor aan de muur, Rack-montage



Beheerfuncties		Prestatie	
Switch type *	Unmanaged	Fanloos	✓
Poorten & interfaces		Minimale systeemeisen	Microsoft Windows 98SE, NT, 2000, XP, Vista, Windows 7, MAC OS, NetWare, UNIX, Linux
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Technische details	
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)	Certificaten van naleving	CE, Federal Communications Commission (FCC), RoHS
Fast Ethernet (koperen) ports kwantiteit	16	Energie	
Netstekker	DC-in ingang	Stroombron *	DC
Netwerk		Vermogenstoevoer inclusief *	✓
Netwerkstandaard *	IEEE 802.3u, IEEE 802.3x	DC voltage input	9 V
10G support *	✗	Stroom	0.6 A
Koperen ethernetbekabelingstechnologie	100BASE-TX, 10BASE-T	Vermogensverbruik (max)	3,23 W
Full duplex	✓	Power over Ethernet (PoE)	
Half-duplex	✓	Power over Ethernet (PoE) *	✗
Datastroombeheer	✓	Eisen aan de omgeving	
Auto MDI/MDI-X	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Temperatuur bij opslag	-40 - 70 °C
Auto-negotiation	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
MAC-adres zelflerende functie	✓	Luchtvochtigheid bij opslag	5 - 90 procent
Data-uitwisseling		Warmtedissipatie	11,01 BTU/h
Switchingcapaciteit *	3,2 Gbit/s	Gewicht en omvang	
MAC-adrestabel *	2000 entries	Breedte	200 mm
Store-and-forward	✓	Diepte	142 mm
Design		Hoogte	40 mm
Rack-montage *	✓	Verpakking	
Stapelbaar *	✗	Gebruiksaanwijzing	✓
Kleur van het product	Zwart	Inclusief AC-adapter	✓
LED-indicatoren	✓	Type verpakking	Doos
Ophangstelsysteem voor aan de muur	✓	Breedte verpakking	223 mm

Verpakking

Diepte verpakking	285 mm
Hoogte verpakking	68 mm
Gewicht verpakking	590 g

Duurzaamheid

Naleving van duurzaamheid	✓
---------------------------	---



0845973020293



845973020293



6935364020293

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.