




TP-Link TL-SF1005D Managed Fast Ethernet (10/100) Wit

Merk : TP-Link

Artikelcode: TL-SF1005D V15

Productnaam : TL-SF1005D

TP-Link TL-SF1005D. Switch type: Managed. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 5. Full duplex. MAC-adrestabel: 1000 entries, Switchingcapaciteit: 1,6 Gbit/s. Netwerkstandaard: IEEE 802.3u, IEEE 802.3x. DC voltage input: 5 V. Netstekker: DC-in ingang



Beheerfuncties		Prestatie	
Switch type *	Managed	Fanloos	✓
Quality of Service (QoS)	✓	Technische details	
Web-gebaseerd management	✓	Certificaten van naleving	CE, Federal Communications Commission (FCC), RoHS
Poorten & interfaces		Energie	
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Stroombron *	DC
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)	Vermogenstoevoer inclusief *	✗
Fast Ethernet (koperen) ports kwantiteit	5	AC-ingangsspanning	220 V
Netstekker	DC-in ingang	AC-ingangsfrequentie	50 Hz
Netwerk		DC voltage input	5 V
Netwerkstandaard *	IEEE 802.3u, IEEE 802.3x	Stroom	0.6 A
10G support *	✗	Stroomverbruik (typisch)	1,87 W
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-T	Vermogensverbruik (max)	1,87 W
Full duplex	✓	Power over Ethernet (PoE)	
Datastroombeheer	✓	Power over Ethernet (PoE) *	✗
Auto MDI/MDI-X	✓	Eisen aan de omgeving	
Spanning tree protocol	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Temperatuur bij opslag	-40 - 70 °C
Auto-negotiation	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Data-uitwisseling		Luchtvochtigheid bij opslag	5 - 90 procent
Switchingcapaciteit *	1,6 Gbit/s	Warmtedissipatie	6,38 BTU/h
MAC-adrestabel *	1000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	103,5 mm
Protocollen		Diepte	70 mm
Ondersteunde netwerkprotocollen	CSMA/CD, TCP/IP	Hoogte	22 mm
Design		Verpakking	
Rack-montage *	✗	Meegeleverde kabels	AC
Kleur van het product	Wit	Gebruiksaanwijzing	✓
		Inclusief AC-adapter	✓

Design		Verpakking	
LED-indicatoren	✓	Type verpakking	Doos
Certificering	FCC, RoHs	Breedte verpakking	91 mm
		Diepte verpakking	108 mm
		Hoogte verpakking	85 mm
		Gewicht verpakking	190 g
Duurzaamheid			
		Naleving van duurzaamheid	✓



6935364020064

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date