

# NF-A8 ULN

# Noctua NF-A8 ULN Premium Fan



The NF-A8 is a highly optimised, premium quality quiet 80mm fan. Featuring Noctua's AAO (Advanced Acoustic Optimisation) frame as well as sophisticated aerodynamic design measures such as Flow Acceleration Channels, the NF-A8 further improves the renowned quiet cooling performance of the award-winning NF-R8. The ULN version provides super-slow 1400/1100rpm speed settings for ultra-low-noise applications and highly noise sensitive users who demand near-silent operation. Its superb running smoothness, reference-class SSO2 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

### Succeeding the award-winning NF-R8

Noctua's NF-R8 fan has become a default-choice among PC enthusiasts looking for a premium quality quiet 80mm fan. Thanks to its thoroughgoing aerodynamic optimisations, the NF-A8 provides higher static pressure and an even better airflow/noise ratio than its much acclaimed predecessor.

### Flow Acceleration Channels

The NF-A8 impeller features suction side Flow Acceleration Channels. By speeding up the airflow at the crucial outer blade regions, this measure reduces suction side flow separation and thus leads to better efficiency and lower vortex noise.

### AAO Frame

Noctua's AAO (Advanced Acoustic Optimisation) frames feature integrated anti-vibration pads as well as Noctua's proprietary Stepped Inlet Design and Inner Surface Microstructures, both of which further refine the fan's performance/noise efficiency.

### Stepped Inlet Design

Noctua's Stepped Inlet Design adds turbulence to the influx in order to facilitate the transition from laminar flow to turbulent flow, which reduces tonal intake noise, improves flow attachment and increases suction capacity, especially in space restricted environments.

### Inner Surface Microstructures

With the tips of the fan blades ploughing through the boundary layer created by the Inner Surface Microstructures, flow separation from the suction side of the blades is significantly suppressed, which results in reduced blade passing noise and improved airflow and pressure efficiency.

### Smooth Commutation Drive 2

The latest version of Noctua's advanced Smooth Commutation Drive system ensures superb running smoothness by eliminating torque variations and switching noises. This makes the NF-A8 remarkably quiet even at very close distance.

### SSO2 Bearing

The NF-A8 features the further optimised second generation of Noctua's renowned, time-tested SSO bearing. With SSO2, the rear magnet is placed closer to the axis to provide even better stabilisation, precision and durability.

### 2 speed settings for maximum quietness

Providing 1400 and 1100 rpm speed settings via the supplied adapter, the ULN (Ultra-Low-Noise) version is tailor made for serious silent enthusiasts who demand super-slow running speeds and utmost quietness of operation.

### Extensive cabling options

The fan's short 20cm primary cable minimises cable clutter in typical applications while the supplied 30cm extension provides extended reach when necessary. Both cables are fully sleeved and the supplied 3:4 pin adaptor allows to connect the fan directly to the power supply.

### 6 years manufacturer's warranty

Noctua fans are renowned for their impeccable quality and outstanding longevity. Like all Noctua fans, the NF-A8 ULN features an MTBF rating of more than 150.000 hours and comes with a full 6 years manufacturer's warranty.

## LOGISTICAL DATAS

Product Labeling  
**Noctua NF-A8 ULN**  
 EAN-No.  
**471612331549-0**  
 UPC-No.  
**84243101446-7**  
 Dimensions (HxWxD)  
**210 x 150 x 34 mm**  
 Weight  
**235 gr**  
 Warranty  
**6 Years**  
 MSPR  
**15.90 EUR**  
 Packaging Unit  
**40 Pcs.**  
 Dimensions / Unit (HxWxD)  
**390 x 370 x 360 mm**  
 Weight / Unit  
**11.1 kg**

## SCOPE OF DELIVERY

NF-A8 ULN Premium Fan  
 Low-Noise Adaptor (L.N.A.)  
 3:4 Pin Adaptor  
 30cm Extension Cable  
 4x Anti-Vibration Mounts  
 4x Fan Screws



## SPECIFICATIONS

Size	80 x 80 x 25 mm	
Bearing	SSO2	
Blade Geometry	A-Series with Flow Acceleration Channels	
Max. Input Power/Operating Voltage	0.60 W/12V	
MTBF	> 150.000 h	

NF-A8 ULN	w/o adaptor	with L.N.A.
Max. Rotational Speed (+/-10%)	1400 RPM	1100 RPM
Max. Airflow	34.8 m³/h	25.6 m³/h
Max. Acoustical Noise	10.4 dB(A)	6.5 dB(A)
Max. Static Pressure	1.05 mmH2O	0.61 mmH2O

Designed in Austria, Noctua's premium cooling components are internationally renowned for their superb quietness, exceptional performance and thoroughgoing quality. Having received more than 3000 awards and recommendations from leading hardware websites and magazines, Noctua's fans and heatsinks are chosen by more than a hundred thousand satisfied customers around the globe.

[www.noctua.at](http://www.noctua.at)