



SL-500 PLUS-
The consequent development of the SL-500.

The **SL-500 PLUS** provides the customers with a high efficiency of at least 82% and therefore protects environment and wallet.

With four S-ATA- and three Molex-connectors, 4+4pin- and 20+4pin-connectors the power supply offers a lot of options for configuration. The **SL-500 PLUS** finds its usage in older and new computer systems.

Specifications


Output	500W
Mainboard 20+4Pin	1x
4Pin/ 4+4Pin/ 8Pin 12V	-/•/-
PCI-Express 6+2Pin	-
PCI-Express 6Pin	-
IDE 4Pin	3x
S-ATA	4x
Floppy	1x
Fan Monitoring	-
115/230V Input	-/•
PFC	Aktive
ATX-Standard	ATX 2.4
Fan Dimensions	120mm
Fan Control	Auto.
Noise Level	19-25dB
Cable Management	-
PSU Dimensions (H/W/D)	86/150/140mm
Package Dimensions (H/W/D)	90/215/165mm
Weight (net)	0.99Kgs
Weight (gross)	1.28Kgs
Packing Units (VE/VPE/PAL)	1/10/350
Guarantee and Warranty	24 Months Guarantee
Article Number	88882140
EAN-Code	4260133129108
Scope of Delivery	Manual Power cable Velcro cable ties
80+ Certificate	-

- = existing
- = non existing

Certification:



Connectors



AC Input	VOLTAGE			CURRENT		FREQUENCY		
	230V			3A		50-60Hz		
DC Output	+3.3V	+5V	+12V1	-12V	+5VsB	PS-ON	POK	COM
	15A	16A	30A	0.8A	2.5A	REMOTE	P.G.	RETURN
MAX	120W		360W	9.6W	12.5W	-	-	-
	500W					-	-	-