D-Link

D-Link DGS-1210-20 netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) 1U Zwart

Merk : D-Link

Artikelcode: DGS-1210-20

Productnaam : DGS-1210-20


D-Link DGS-1210-20. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernetpoorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 40 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Netstekker: AC-in-aansluiting. Rack-montage, Vormfactor: 1U






Management features		Security	
Switch type * Switch layer Quality of Service (QoS) support	Managed L2	DHCP features Access Control List (ACL) IGMP snooping	DHCP server, DHCP client
Web-based management ARP inspection Configuring Location Settings (CLI) System event log		MAC address filtering Loop protection Multicast features Multicast support	•
MIB support	 Image: A start of the start of	Design	
Ports & interfaces Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports type * Combo SFP ports quantity	Gigabit Ethernet (10/100/1000) 4	Rack mounting * Stackable * Form factor Product colour LED indicators	✓ ✓ 1U Black ✓
Power connector	AC-in jack	Performance	
Network Networking standards * Copper ethernet cabling technology Port mirroring	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x 10BASE-T, 100BASE-TX, 1000BASE- T	Memory type Internal memory Flash memory Noise level Mean time between failures (MTBF)	DDR3-SDRAM 256 MB 32 MB 0 dB 1087100 h
Full duplex	1	Power	
Flow control support Link aggregation Broadcast storm control Auto MDI/MDI-X Spanning tree protocol		Power source * Power supply included * AC input voltage AC input frequency Power consumption (max)	AC ✓ 100 - 240 V 50/60 Hz 13.08 W
Head-of-line (HOL) blocking	- -	Power over Ethernet (PoE)	
Auto-negotiation VLAN support	- / /	Power over Ethernet (PoE) *	×

Network		Operational conditions	
Number of VLANs Data transmission Switching capacity * Forwarding rate	ata transmissionwitching capacity *40 Gbit/sorwarding rate77.4 MppsAC address table *8000 entriesore-and-forwardmbo frames supportmbo frames10000	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Heat dissipation	-5 - 50 °C -20 - 70 °C 0 - 95% 0 - 95% 44.62 BTU/h
MAC address table * Store-and-forward Jumbo frames support Jumbo frames Packet buffer memory		Weight & dimensions Width Depth Height Weight	280 mm 180 mm 44 mm 1.75 kg















Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.