

# Rittal – The System.

Faster – better – everywhere.

## **Component shelf, static installation for 482.6 mm (19") system punchings, depth-variable for TS IT, TE – DK 5501.655**

Date : Jul 27, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP




# Component shelf, static installation for 482.6 mm (19") system punchings, depth-variable for TS IT, TE – DK 5501.655

created: 27.07.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Benefits:</b>	Tool-free, time-saving one-man assembly
<b>Applications:</b>	Depth-variable to adapt to individual distances between levels
<b>Material:</b>	Sheet steel
<b>Surface finish:</b>	Spray-finished
<b>Colour:</b>	RAL 9005
<b>Supply includes:</b>	Assembly parts
<b>Packs of:</b>	1 pc(s).
<b>EAN:</b>	4028177679092
<b>Customs tariff number:</b>	73269098
<b>eCl@ss 5.1:</b>	27189218
<b>eCl@ss 7.0:</b>	27189261
<b>ETIM 6.0:</b>	EC002620

Product features	
To fit:	Enclosure type: TS IT Enclosure type: TE 7000 Enclosure type: TE 8000
Dimensions:	Width: 484 mm
Installation options:	482.6 mm (19") L mounting angles, front and rear 482.6 mm (19") mounting frames front and rear
Distance between levels:	min.: 400 mm max.: 600 mm
Units:	0.5 U
Load capacity:	50 kg
Weight/pack:	6.56 kg
Downloads	
Documentation:	 <a href="#">Instructions (FR, EN, DE)</a>
CAD drawings:	Request