Canon

Canon imageFORMULA DR-6030C ADF-scanner 600 \times 600 DPI A3 Wit

Merk : Canon Productfamilie: Artikelcode: 4624B003

imageFORMULA

Productnaam: DR-6030C



DR6030C - CMOS CIS, 600 dpi, RGB LED, A3, 300 x 432mm, USB 2.0, SCSI-3, 80ppm, 10.5kg Canon imageFORMULA DR-6030C. Maximum scanformaat: 300 x 432 mm, Optische scanresolutie: 600 x 600 DPI, Kleurdiepte invoer: 24 Bit. Soort scanner: ADF-scanner, Kleur van het product: Wit. Type beeldsensor: CMOS CIS, Dagelijkse diensten cyclus (max): 10000 pagina's, Lichtbron: RGB LED. Standaard invoercapaciteit: 100 vel. Maximale ISO A-series papierformaat: A3, ISO A-series afmetingen (A0...A9): A3, Media dikheid (min): 0,05 mm

Scanning		Power	
Maximum scan size * Optical scanning resolution * Colour scanning Duplex scanning *	300 x 432 mm 600 x 600 DPI	Power supply type * Power consumption (typical) AC input frequency Input voltage	AC 46.5 W 50 - 60 Hz 220-240 V
Input colour depth	24 bit	Weight & dimensions	
Film scanning Greyscale levels Design	× 256	Width Depth Height	398 mm 668 mm 194 mm
Scanner type *	ADF scanner	Weight	10.5 kg
Product colour *	White	Packaging content	
Built-in display *	×	Bundled software	CapturePerfect 3.0, Kofax VRS Basic, Adobe Acrobat 9 Standard
Performance Sensor type *	CMOS CIS	Sustainability	
Light source	RGB LED	Sustainability certificates	ENERGY STAR
Daily duty cycle (max) *	10000 pages	System requirements	
Scan drivers	ISIS, TWAIN	Windows operating systems supported	Windows 2000 Professional, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Professional
Input capacity	100 sheets		
Standard input capacity	100 Sheets		
Maximum ISO A-series paper size * ISO A-series sizes (A0A9) Media thickness (min)	A3 A3 0.05 mm		
USB version 2	2.0 SCSI-3, USB 2.0		
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	10 - 32.5 °C 20 - 80%
		Other features	
		Output resolutions	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
		Certification	RoHS
		Logistics data	0.474.607.0
		Harmonized System (HS) code	84716070











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.