

Delock PCI Express Card > 8 x Serial RS-232 High Speed 921K

Description

The Delock PCI Express card expands your system by eight High Speed RS-232 ports. Use this card for applications like data logging, machine control systems, automation, development or communication. By the extensive surge protection and the wide temperature range this card can be used in the industrial area.



Specification

- Chipset: Exar 17V358
- Connector:
 - external:
 - 1 x VHDICI 68 Pin female
 - connecting cable: VHDICI 68 Pin male > 8 x Serial RS-232
 - Sub-D 9 pin male
 - internal:
 - 1 x PCI Express x1, V2.0
- Baud rate: up to 921.6 Kb/s
- Compatible to 16C550 UART
- FIFO 256 Byte
- Data bit: 5, 6, 7, 8
- Stop bit: 1, 1.5, 2
- Parity: None, Even, Odd, Space, Mark
- Flow Control: RTS / CTS, XON / XOFF
- Operating temperature: -30 °C ~ +75 °C
- Storage temperature: -40 °C ~ +85 °C
- Ambient relative humidity max. 95 % (non-condensing)
- 15 kV ESD protection for all signals
- I/O address and IRQ assigned by the system

Item No. 89336



EAN 4043619893362

Country of origin Taiwan, Republic of
China

System requirements

- Windows XP/XP-64/Vista/Vista-64/7/7-64, Linux ex Kernel 2.6
- PC with a free PCI Express slot

Package content

- PCI Express card
- Low profile bracket
- 1 serial connecting cable (ca. 30 cm)
- Driver CD
- User manual

Package

- Box

Images

