D-Link

D-Link DPE-301GI PoE adapter & injector Fast Ethernet, Gigabit Ethernet

Merk: D-Link Artikelcode: DPE-301GI

Productnaam: DPE-301GI

D-Link DPE-301Gl. Ethernet interface type: Fast Ethernet, Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s, Bekabelingstechnologie: 10/100/1000. Kleur van het product: Wit. AC-adapter ingangsspanning: 100 - 240 V, AC-adapterfrequentie: 50/60 Hz, Output current: 0,6 A. Certificering: CE, FCC, VCCI, RCM. Breedte: 62,2 mm, Diepte: 109,8 mm, Hoogte: 24,5 mm





Network		Weight & dimensions	
Ethernet interface type Ethernet LAN data rates Cabling technology Power over Ethernet (PoE)	Fast Ethernet, Gigabit Ethernet 10,100,1000 Mbit/s 10/100/1000	Height	24.5 mm
		Weight	70 g
		Packaging content	
		Number of products included	1 pc(s)
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u	Packaging data	
Features		Package width	153 mm
Product colour	White	Package depth	213 mm
Wall mountable	✓	Package height	68 mm
Easy to install	✓	Package weight	398 g
Rack mounting	×	Logistics data	
Plug and Play	√	Shipping (inner) case length	32.6 cm
LED indicators	·	Shipping (inner) case width	23.3 cm
	•	Shipping (inner) case height	36 cm
Ports & interfaces		Shipping (inner) case net weight	4.1 kg
Ethernet LAN (RJ-45) ports	2	Products per shipping (inner) case	10 pc(s)
DC-in jack	✓	Pallet gross weight (air)	297.8 kg
Power		Master (outer) cases per pallet (air)	• • •
AC adapter input voltage	100 - 240 V	Products per pallet (air) Pallet gross length	600 pc(s) 120 cm
AC adapter frequency	50/60 Hz	Pallet gross width	110 cm
Output current	0.6 A	Pallet height (air)	194 cm
Power consumption (max)	32.4 W	Pallet gross weight (sea)	297.8 kg
Certificates		Master (outer) cases per pallet (sea)	60 pc(s)
Certification	CE, FCC, VCCI, RCM	Products per pallet (sea)	600 pc(s)
Operational conditions		Pallet height (sea) Shipping (inner) case gross weight	194 cm 4.63 kg
Operating temperature (T-T)	-10 - 50 °C	Harmonized System (HS) code	85044095
Operating relative humidity (H-H)	5 - 95%	Harmonized System (HS) code	03044033
Storage temperature (T-T)	-30 - 70 °C		
Storage relative humidity (H-H)	5 - 95%		
Weight & dimensions			
Width	62.2 mm		
Depth	109.8 mm		





790069416668

0790069416668



5054629910450

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.