



IPC 1U-1404

The **IPC 1U-1404** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 1U-1404** offers the possibility to install maximal four 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD external and three internal 2.5" HDDs. The **IPC 1U-1404** has five 40mm fans included, which are mounted directly at the back of the drive brackets and ensure therefore a reliable and optimal cooling.

Additional extras like the reusable and perforated slot bracket, the universal slot bracket and the lid with the snap locks round off the picture.

Specifications

Motherboard	Mini ITX, μ ATX, ATX, eATX, SSI EEB
Drive Bays	4x 2.5" or 3.5" Hot-Swap 1x drive bay Slim DVD for 1x Slim DVD or 1x 2.5" internal hard drive 2x drive bays 2.5" for 1x 2.5" internal hard drive
Front connectors	USB 2.0: 2
Cooling System	Internal: 10x 40mm (5x included, Molex connector and 5x optional)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	1HU Server Power Supply
Material	1.0/1.2mm Steel
Packing Unit	Shipping Unit: 1 piece Pallet: 27 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887115
EAN-Code	4260133126367
Scope of Delivery	Screw Set Assembly tool Mounting brackets for 1HU PSU 5x 40mm fan included Drive brackets removable Reusable and perforated slot bracket (rear) Universal slot bracket (rear) Lid with snap locks USB 2.0 as block connector Hot-Swap backplane with SFF-8087 connectors*
Optional Accessories	Lockable frontgrill 1HU silver (Article number: 88887114)

*The included backplanes only support SAS-Controller with SFF-8087 connection.
In operation with SATA-Controllers, please order the optional available SFF8087 cross-over cables (Art.-No. 88885237) in right quantity.

Dimensions and Weight

	Cage	Case	Package
Height	45mm	45mm	110mm
Width	433mm	482mm	560mm
Depth	650mm	685mm	830mm

Weight (net): 7.94 kg
Weight (gross): 10.02 kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

