



LevelOne SFP-3611 netwerk transceiver module Vezel-optiek 1250 Mbit/s 1550 nm

Merk : LevelOne

Artikelcode: SFP-3611

Productnaam : SFP-3611



SFP-3611

LevelOne SFP-3611 netwerk transceiver module Vezel-optiek 1250 Mbit/s 1550 nm:

1550nm DFB LD

Data Rate: 1.25Gbps,NRZ

Single +3.3V Power Supply

RoHS Compliant and Lead-free

AC/AC Differential Electrical Interface

Compliant with Multi-Source Agreement(MSA)

Duplex LC Connector

Compliance with specifications for IEEE-802.3z Gigabit Ethernet at 1.25Gbps

Compliance with ANSI specifications for Fibre Channel applications at 1.06Gbps

No configuration or installation software required

Eye Safety Designed to meet LASER Class 1 comply with EN60825-1

LevelOne SFP-3611. SFP transceiver type: Vezel-optiek, Maximale overdrachtssnelheid van gegevens:

1250 Mbit/s, Soort aansluiting: SFP. Ingangsspanning: 3.3 V, Maximaal voltage: 6 V, Stroom (max.): 300

A. Certificaten van naleving: RoHS, Veiligheid: EN 60825-1, Certificering: CE, FCC. Breedte: 57 mm,

Diepte: 12 mm, Hoogte: 13,7 mm. Aantal per verpakking: 1 stuk(s)



Prestatie		Certificaten	
SFP transceiver type *	Vezel-optiek	Certificaten van naleving	RoHS
Maximale overdrachtssnelheid van gegevens *	1250 Mbit/s	Veiligheid	EN 60825-1
Soort aansluiting *	SFP	Certificering	CE, FCC
Single-mode glasvezelkabel (SMF) ondersteund	✓	Eisen aan de omgeving	
Vezel-optische connector	LC	Bedrijfstemperatuur (T-T)	0 - 70 °C
Vezelkabel diameters ondersteund	9/125 µm	Temperatuur bij opslag	-40 - 85 °C
Maximaal bereik	80000 m	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Golflengte	1550 nm	Gewicht en omvang	
Tx vermogen (min)	0 dBmW	Breedte	57 mm
Tx vermogen (max)	5 dBmW	Diepte	12 mm
Link budget	23 dB	Hoogte	13,7 mm
Netwerkstandaard	IEEE 802.3z	Gewicht	20 g
Duplex systeem	Volledig	Inhoud van de verpakking	
Fibre channel-poorten	1	Aantal per verpakking	1 stuk(s)
Kenmerken		Verpakking	
Plug and play	✓	Breedte verpakking	106 mm
Hot-swap	✓	Diepte verpakking	20 mm
Energie		Hoogte verpakking	65 mm
Ingangsspanning	3.3 V	Gewicht verpakking	35 g
Maximaal voltage	6 V	Logistieke gegevens	
Stroom (max.)	300 A	Code geharmoniseerd systeem (HS) 85369010	



4015867155172



4015867240304

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.