



LevelOne IEC-4301 netwerk media converter 100 Mbit/s Single-mode Zwart

Merk : LevelOne

Artikelcode: IEC-4301

Productnaam : IEC-4301



LevelOne IEC-4301. Maximale overdrachtssnelheid van gegevens: 100 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, Converter output interface: 100Base-FX. Vezel-optische connector: SC, Connectiviteitstechnologie: Bedraad. Maximaal bereik: 30000 m, Draad modus structuur: Single-mode. LED-indicatoren: Activiteit, Link, Stroom, Kleur van het product: Zwart, Materiaal behuizing: Aluminium. Ingangsspanning: 12 - 60 V, Stroomverbruik (typisch): 1,44 W



Netwerk		Design	
Maximale overdrachtssnelheid van gegevens *	100 Mbit/s	Certificering	FCC Part 15 Subpart B Class A CE EN 55022 Class A FCC Part 15 Subpart B Class A, CE EN 55022 Class A EN61000-4-2 (ESD) Level 3 EN61000-4-3 (RS) Level 2 EN61000-4-4 (EFT) Level 2 EN61000-4-5 (Surge) Level 2 EN61000-4-6 (CS) Level 2 EN 61000-4-8 (PFMF) Level 1 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6
Converter input interface	10Base-T, 100Base-TX		
Converter output interface	100Base-FX		
Netwerkstandaard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x		
Ethernet interface type	Fast Ethernet		
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s		
Auto MDI/MDI-X	✓		
Auto-negotiation	✓		
Store-and-forward	✓		
Duplex systeem	Volledig, Half		
Poorten & interfaces		Energie	
Connectiviteitstechnologie	Bedraad	Ingangsspanning	12 - 60 V
Aantal Ethernet LAN (RJ-45)-poorten	1	Stroomverbruik (typisch)	1,44 W
Fibre channel-poorten	1	Gewicht en omvang	
Vezel-optische connector *	SC	Breedte	59 mm
Prestatie		Diepte	49 mm
Maximaal bereik *	30000 m	Hoogte	36 mm
Draad modus structuur	Single-mode	Gewicht	90 g
Design		Eisen aan de omgeving	
Intern *	✗	Bedrijfstemperatuur (T-T)	-40 - 75 °C
LED-indicatoren	Activiteit, Link, Stroom	Temperatuur bij opslag	-40 - 75 °C
Kleur van het product	Zwart	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Materiaal behuizing	Aluminium	Verpakking	
Land van herkomst	Taiwan	Breedte verpakking	160 mm
		Diepte verpakking	105 mm
		Hoogte verpakking	65 mm
		Gewicht verpakking	260 g
		Type verpakking	Doos
		Inhoud van de verpakking	
		Snelle installatiehandleiding	✓

Technische details

Duurzaamheidscertificaten RoHS

Logistieke gegevens

Code geharmoniseerd systeem (HS) 85176990



4015867188163

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-MAR-2024. Prints or copies of Information are only valid on the printed Publication date