




LevelOne IES-0600 netwerk-switch Gigabit Ethernet (10/100/1000) Zwart

Merk : LevelOne

Artikelcode: IES-0600

Productnaam : IES-0600

LevelOne IES-0600. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 4. Full duplex. MAC-adrestabel: 1024 entries, Switchingcapaciteit: 12 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Ophangstelsysteem voor aan de muur



Poorten & interfaces		Design	
Aantal basis-switching RJ-45 Ethernet-poorten *	4	Certificering	FCC Part 15 Subpart B Class A CE EN 55022 Class A EN61000-4-2 (ESD) Level 3 EN61000-4-3 (RS) Level 3 EN61000-4-4 (EFT) Level 3 EN61000-4-5 (Surge) Level 3 EN61000-4-6 (CS) Level 3 EN61000-4-8 (Magnetic Field) Level 3 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6 UL 508
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)		
Aantal moduleslots SPF	1		
Netwerk			
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z		
10G support *	✗	Energie	
Full duplex	✓	Ingangsspanning	5 - 56 V
Datastroombeheer	✓	Stroomspanning bescherming	Overbelasting, Omgekeerde polariteit
Auto MDI/MDI-X	✓		
Auto-negotiation	✓		
Data-uitwisseling		Power over Ethernet (PoE)	
Switchingcapaciteit *	12 Gbit/s	Power over Ethernet (PoE) *	✗
MAC-adrestabel *	1024 entries	Eisen aan de omgeving	
Store-and-forward	✓	Bedrijfstemperatuur (T-T)	-40 - 75 °C
Jumbo frames	10000	Temperatuur bij opslag	-40 - 85 °C
Packet forwarding rate (1 Gbps)	1488000 pps	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Packet forwarding rate (100 Mbps)	148000 pps	Luchtvochtigheid bij opslag	5 - 95 procent
Packet forwarding rate (10 Mbps)	14880 pps		
Packet buffergeheugen	1 MB	Gewicht en omvang	
Design		Breedte	40 mm
Kleur van het product	Zwart	Diepte	105 mm
Materiaal behuizing	Metaal	Hoogte	38 mm
LED-indicatoren	Activiteit, Link, Stroom	Gewicht	720 g
Internationale veiligheidscode (IP)	IP30	Verpakking	
Ophangstelsysteem voor aan de muur	✓	Snelstartgids	✓
DIN rail bevestiging	✓	Type verpakking	Doos
Land van herkomst	Taiwan	Breedte verpakking	215 mm
		Diepte verpakking	165 mm
		Hoogte verpakking	65 mm
		Gewicht verpakking	120 g
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85176990	
		Overige specificaties	
		Klemmenblokpoort	✓



4015867188491



4015867224250

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date