

CyberPower PR2200ELCDSL UPS Line-interactive 2,2 kVA 1980 W 9 AC-uitgang(en)

Merk : CyberPower

Artikelcode: PR2200ELCDSL

Productnaam : PR2200ELCDSL

CyberPower PR2200ELCDSL. UPS-topologie: Line-interactive, Output power capacity: 2,2 kVA, Uitgangsvermogen: 1980 W. Stopcontacttypes: C13 stekker, C19 stekker, Stekker: C20 stekker, Aantal AC uitgangen: 9 AC-uitgang(en). Batterijtechnologie: Sealed Lead Acid (VRLA), Batterij capaciteit: 9 Ah, Accu/Batterij voltage: 12 V. Vormfactor: Tower, Kleur van het product: Zwart, Type beeldscherm: LCD. Breedte: 170 mm, Diepte: 432 mm, Hoogte: 221 mm



Kenmerken		Accu/Batterij	
UPS-topologie *	Line-interactive	Batterijtechnologie	Sealed Lead Acid (VRLA)
Output power capacity *	2,2 kVA	Batterij capaciteit	9 Ah
Uitgangsvermogen *	1980 W	Accu/Batterij voltage	12 V
Golfvorm *	Sinus	Ondersteund aantal accu's/batterijen	4
Ingang operation voltage (min) *	160 V	Typische backup tijd op volledige lading	3 min
Ingang operation voltage (max) *	283 V	Typische backup tijd op halve lading	12 min
Frequentie *	50/60 Hz	Accu/Batterij oplaadtijd	8 uur
Automatic Voltage Regulation (AVR)	✓	Automatische batterij test	✓
Responstijd	4 ms	Design	
Aantal input fases	1	Vormfactor *	Tower
Aantal output fases	1	Kleur van het product *	Zwart
Emergency Power Off (EPO)	✓	Type beeldscherm	LCD
EMI/RFI geluidsfiltering	✓	LED-indicatoren	✓
Spanningsbeveiliging	✓	Gewicht en omvang	
Stroomspanning bescherming	Overbelasting	Breedte	170 mm
Geluidsalarm(en)	✓	Diepte	432 mm
Web-gebaseerd management	✓	Hoogte	221 mm
Beheerprotocollen	SNMP, HTTP	Gewicht	23,3 kg
Auto-herstart	✓	Verpakking	
Poorten & interfaces		Meegeleverde software	PowerPanel Business Edition
Stopcontacttypes	C13 stekker, C19 stekker	Overige specificaties	
Stekker	C20 stekker	Output-aansluitingen	8 x IEC 320 C13, 1 x IEC 320 C19
Aantal AC uitgangen	9 AC-uitgang(en)	Netspanning, in bedrijf	230 V
Aantal USB 2.0-poorten	1	Nominale input voltage	230 V
Seriële poort(en)	1	Geschikt voor gebruik in land/locatie	Europa
Noodstop-aansluiting (EPO)	✓		



4712364146350

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.