

CyberPower UT1050EG UPS Line-interactive 1,05 kVA 630 W 4 AC-uitgang(en)

Merk : CyberPower

Artikelcode: UT1050EG

Productnaam : UT1050EG

CyberPower UT1050EG. UPS-topologie: Line-interactive, Output power capacity: 1,05 kVA, Uitgangsvermogen: 630 W. Stopcontacttypes: Type F, Aantal AC uitgangen: 4 AC-uitgang(en), Bekabelingstechnologie: 10/100/1000Base-T(X). Batterijtechnologie: Sealed Lead Acid (VRLA), Accu/Batterij oplaadtijd: 6 uur. Vormfactor: Tower, Kleur van het product: Zwart, Materiaal behuizing: Kunststof. Certificaten van naleving: RoHS, Certificering: CE, EAC



Kenmerken		Poorten & interfaces	
UPS-topologie *	Line-interactive	Aantal Ethernet LAN (RJ-45)-poorten	2
Output power capacity *	1,05 kVA	Bekabelingstechnologie	10/100/1000Base-T(X)
Uitgangsvermogen *	630 W	Accu/Batterij	
Golfvorm *	Sinus	Batterijtechnologie	Sealed Lead Acid (VRLA)
Ingang operation voltage (min) *	165 V	Accu/Batterij oplaadtijd	6 uur
Ingang operation voltage (max) *	290 V	Design	
Frequentie *	50/60 Hz	Vormfactor *	Tower
Uitgang operation voltage (max)	230 V	Materiaal behuizing	Kunststof
Output frequentie	50/60 Hz	Kleur van het product *	Zwart
Automatic Voltage Regulation (AVR)	✓	LED-indicatoren	✓
Surge energy rating	150 J	Eisen aan de omgeving	
Responstijd	4 ms	Bedrijfstemperatuur (T-T)	0 - 40 °C
Aantal input fases	1	Temperatuur bij opslag	-20 - 50 °C
EMI/RFI geluidsfiltering	✓	Relatieve vochtigheid in bedrijf (V-V)	0 - 90 procent
Golf protectie functies	Digital Subscriber Line (DSL), Faxen, Modem, Netwerk	Luchtvochtigheid bij opslag	0 - 90 procent
Stroomspanning bescherming	Overbelasting, Kortsluiting	Hoogte, in bedrijf	0 - 3000 m
Geluidsalarm(en)	✓	Hoogte bij opslag	0 - 3000 m
Hoorbare alarmstanden	Alarm bij werking op batterij, Storing, Alarm bij laag batterijniveau, Alarm bij overbelasting	Certificaten	
Poorten & interfaces		Certificaten van naleving	RoHS
Stopcontacttypes	Type F	Certificering	CE, EAC
Aantal AC uitgangen	4 AC-uitgang(en)	Gewicht en omvang	
USB-poort	✓	Breedte	95 mm
		Diepte	307 mm
		Hoogte	220 mm
		Gewicht	6,9 kg



4712856273519

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.