


Beeldscherm		Eisen aan de omgeving	
Hardheid oppervlak	3H	Relatieve vochtigheid in bedrijf (V-V)	20 - 80 procent
RGB-kleurruimte	sRGB	Hoogte, in bedrijf	0 - 3658 m
sRGB-dekking (gemiddeld)	123,9 procent	Hoogte bij opslag	3658 - 12192 m
NTSC-dekking (normaal)	106 procent	Inhoud van de verpakking	
Adobe RGB dekking	90,4 procent	Staander inbegrepen	✓
sRGB	✓	Meegeleverde kabels	HDMI, DisplayPort, AC
Prestatie		Gebruikershandleiding	✓
NVIDIA G-SYNC *	✗	Gewicht en omvang	
AMD FreeSync *	✓	Breedte apparaat (met standaard)	540 mm
AMD FreeSync-type	FreeSync Premium	Diepte apparaat (met standaard)	213 mm
Component video sync	Separate sync	Hoogte apparaat (met standaard)	513 mm
Knippervrije technologie	✓	Gewicht (met standaard)	3,78 kg
Laag-blauw-licht-technologie	✓	Breedte (zonder voet)	540 mm
Lage invoervertraging	✓	Diepte (zonder voet)	43 mm
Compatibele besturingssystemen	Mac OS X Windows 10 / 8.1 / 8 / 7	Hoogte (zonder voet)	321 mm
Multimedia		Gewicht (zonder voet)	2,4 kg
Ingebouwde luidsprekers *	✓	Verpakking	
Ingebouwde camera *	✗	Breedte verpakking	600 mm
Aantal luidsprekers	2	Diepte verpakking	164 mm
Gemiddeld vermogen	6 W	Hoogte verpakking	526 mm
Design		Gewicht verpakking	5,73 kg
Markt positionering *	Gamen	Duurzaamheid	
Kleur van het product *	Zwart	Naleving van duurzaamheid	✓
Voetenkleur	Zwart	Duurzaamheidscertificaten	RoHS
Certificering	CB, CE Mark, FCC Class B, ICES-003, CU-EAC, EAEU RoHS, TUV/ISO9241-307, TUV-BAUART	Bevat geen	Kwik, PVC/BFR
Poorten & interfaces		Europees Productregister voor Energielabeling (EPREL) code	913516
Ingebouwde USB-hub *	✗	Logistieke gegevens	
HDMI *	✓	Code geharmoniseerd systeem (HS)	85285210
Aantal HDMI-poorten	2	Overige specificaties	
HDMI versie	2.0	Glanstype buitenzijde	Getextureerd
Aantal DisplayPorts	1	Beeldverbetering	SmartImage game
DisplayPort versie	1.2	Recyclebaar verpakkingsmateriaal	100 procent
Audio-uitgang	✓	Officiële goedkeuringen	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
HDCP	✓	EasyRead-modus	✓
HDCP versie	2.2	LowBlue-modus	✓
Ergonomie		Energie-efficiëntieklasse (oud)	F
VESA-montage *	✓	Mean time between failures (MTBF)	50000 uur
Paneelmontage-interface	100 x 100 mm		
Bevestigingsmogelijkheid voor kabelslot *	✓		
Kabelslot sleuf type	Kensington		
In hoogte verstelbaar *	✓		



8712581781040

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-APR-2024. Prints or copies of Information are only valid on the printed Publication date