



LevelOne GEP-0821 netwerk-switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs

Merk : LevelOne

Artikelcode: GEP-0821

Productnaam : GEP-0821

8-Port Gigabit PoE Switch

LevelOne GEP-0821. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 8. Full duplex. MAC-adrestabel: 8192 entries, Switchingcapaciteit: 16 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Netstekker: DC-in ingang. Power over Ethernet (PoE). Rack-montage



Poorten & interfaces		Energie	
Aantal basis-switching RJ-45 Ethernet-poorten *	8	Stroom	2 A
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Stroomverbruik (typisch)	130 W
Netstekker	DC-in ingang	Power over Ethernet (PoE)	
Netwerk		Power over Ethernet (PoE) *	✓
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Aantal Power over Ethernet plus (PoE +)-poorten	8
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-TX	Totaal Power over Ethernet (PoE)-budget	123,3 W
Ondersteundende kabel types	Cat5, Cat6, Cat7	Eisen aan de omgeving	
Full duplex	✓	Bedrijfstemperatuur (T-T)	0 - 45 °C
Datastroombeheer	✓	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	16 Gbit/s	Luchtvochtigheid bij opslag	10 - 90 procent
MAC-adrestabel *	8192 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	280 mm
Jumbo Frames ondersteuning	✓	Diepte	185 mm
Jumbo frames	9000	Hoogte	44 mm
Packet forwarding rate (1 Gbps)	1488000 pps	Gewicht	2 kg
Packet forwarding rate (100 Mbps)	148000 pps	Inhoud van de verpakking	
Packet forwarding rate (10 Mbps)	14880 pps	Meegeleverde kabels	AC
Design		Snelstartgids	✓
Rack-montage *	✓	Verpakking	
Kleur van het product	Grijs	Type verpakking	Doos
LED-indicatoren	Activiteit, Power over Ethernet (PoE)	Breedte verpakking	371 mm
Prestatie		Diepte verpakking	230 mm
Buffergrootte	128 KB	Hoogte verpakking	82 mm
Energie		Gewicht verpakking	2,26 kg
AC-ingangsspanning	100 - 240 V	Certificaten	
AC-ingangsfrequentie	50 - 60 Hz	Certificering	FCC, CE

Logistieke gegevens

Land van herkomst	Taiwan
Code geharmoniseerd systeem (HS)	85176990



4015867163849



0777785857791



777785857791

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.