



## LevelOne POR-0101 netwerkextender Netwerkrepeater Zwart

**Merk :** LevelOne

**Artikelcode:** POR-0101

**Productnaam :** POR-0101

PoE Repeater, 1 x 10/100Base-TX RJ-45 PoE, 2.5W, IEEE 802.3/u/x/af/at

LevelOne POR-0101 netwerkextender Netwerkrepeater Zwart:

- 10/100Mbps datadoorvoer via de bekabeling
- Stuur Stroom over Ethernet (802.3af/at PoE) door naar extern apparaat
- Breidt PoE-verbinding met 100 meter uit
- Eenvoudige Plug en Play-installatie, geen extra stroomvoorziening vereist

LevelOne POR-0101. Soort: Netwerkrepeater, Maximaal bereik: 100 m, Overdrachtssnelheid: 100 Mbit/s.

Bekabelingstechnologie: 10/100Base-T(X), Netwerkstandaard: IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Kleur van het product: Zwart, Montagewijze: Muur, LED-indicatoren: Power over Ethernet (PoE), Stroom. Vermogensverbruik (max): 2,5 W, Voltagebereik Power over Ethernet (PoE): 46 - 57 V. Breedte: 80 mm, Diepte: 70 mm, Hoogte: 23 mm



Prestatie		Eisen aan de omgeving	
Soort *	Netwerkrepeater	Bedrijfstemperatuur (T-T)	0 - 50 °C
Maximaal bereik *	100 m	Temperatuur bij opslag	-20 - 70 °C
Overdrachtssnelheid	100 Mbit/s	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Plug and play	✓	Luchtvochtigheid bij opslag	5 - 95 procent
Netwerk		Gewicht en omvang	
Bekabelingstechnologie	10/100Base-T(X)	Breedte	80 mm
Netwerkstandaard	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	Diepte	70 mm
		Hoogte	23 mm
		Gewicht	200 g
Poorten & interfaces		Technische details	
Aantal Ethernet LAN (RJ-45)-poorten	2	Certificaten van naleving	RoHS
Hoeveelheid Power over Ethernet (PoE) ports	2		
Design		Inhoud van de verpakking	
Kleur van het product	Zwart	Snelstartgids	✓
Montagewijze	Muur		
LED-indicatoren	Power over Ethernet (PoE), Stroom	Verpakking	
Land van herkomst	Taiwan	Type verpakking	Doos
Certificering	FCC Part 15, Class B, CE	Breedte verpakking	93 mm
		Diepte verpakking	43 mm
		Hoogte verpakking	140 mm
		Gewicht verpakking	100 g
Energie		Logistieke gegevens	
Vermogensverbruik (max)	2,5 W	Code geharmoniseerd systeem (HS)	85176990
Power over Ethernet (PoE)	✓		
Voltagebereik Power over Ethernet (PoE)	46 - 57 V		



4015867191279

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date