

TP-Link Omada SG3452XP netwerk-switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Zwart

Merk : TP-Link

Productfamilie: Omada

Artikelcode: SG3452XP

Productnaam : SG3452XP



TP-Link Omada SG3452XP. Switch type: Managed, Switch-laag: L2+. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 48, Console port: RJ-45/Micro-USB. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 176 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE.... Netstekker: AC-in-aansluiting. Power over Ethernet (PoE). Rack-montage, Vormfactor: 1U

Beheerfuncties		Beveiliging	
Switch type *	Managed	SSH/SSL support	✓
Switch-laag	L2+	BPDU filtering / bescherming	✓
Quality of Service (QoS)	✓	IP-MAC-Port binding	✓
Web-gebaseerd management	✓	Authenticatie	Auto VLAN, Gast-VLAN
Cloud-beheerd	✓	Multicast-functies	
ARP-inspectie	✓	Multicast-ondersteuning	✓
Locatie-instellingen (CLI) configureren	✓	Design	
System event log	✓	Rack-montage *	✓
Poorten & interfaces		Vormfactor	1U
Aantal basis-switching RJ-45 Ethernet-poorten *	48	Kleur van het product	Zwart
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Reset button	✓
Aantal moduleslots SPF+	4	LED-indicatoren	✓
Console port	RJ-45/Micro-USB	Aantal ventilatoren	3 ventilator(en)
Netstekker	AC-in-aansluiting	Energie	
Netwerk		Stroombron *	AC
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z	Vermogenstoevoer inclusief *	✓
10G support *	✓	AC-ingangsspanning	100 - 240 V
Port mirroring	✓	AC-ingangsfrequentie	50/60 Hz
Datastroombeheer	✓	Vermogensverbruik (max)	635,7 W
Verbindingsaggregatie	✓	Power over Ethernet (PoE)	
Broadcast stormbeheer	✓	Power over Ethernet (PoE) *	✓
Rate limiting	✓	Aantal Power over Ethernet plus (PoE +)-poorten	48
Spanning tree protocol	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Head-of-line (HOL) blocking	✓	Totaal Power over Ethernet (PoE)-budget	500 W
VLAN-ondersteuning	✓	Eisen aan de omgeving	
Data-uitwisseling		Bedrijfstemperatuur (T-T)	0 - 40 °C
Switchingcapaciteit *	176 Gbit/s	Temperatuur bij opslag	-40 - 70 °C
Verzending snelheid	130,9 Mpps	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
MAC-adrestabel *	16000 entries	Luchtvochtigheid bij opslag	5 - 90 procent
Store-and-forward	✓	Warmte-dissipatie	2169,2 BTU/h
Jumbo Frames ondersteuning	✓	Gewicht en omvang	
		Breedte	440 mm

Data-uitwisseling		Gewicht en omvang	
Jumbo frames	9000	Diepte	330 mm
Packet buffergeheugen	12 MB	Hoogte	44 mm
Beveiliging		Inhoud van de verpakking	
DHCP-functies	DHCP client, DHCP relay, DHCP server	Meegeleverde kabels	AC
Access Control List (ACL)	✓	Snelstartgids	✓
IGMP snooping	✓	Certificaten	
MAC adres filtering	✓	Certificering	CE, FCC, RoHS
Statische poort beveiliging	✓		



6935364006495

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.