



TP-Link Omada TL-SG3428XF Managed L2+ 1U Zwart

Merk : TP-Link

Productfamilie: Omada

Artikelcode: SG3428XF

Productnaam : TL-SG3428XF



TP-Link Omada TL-SG3428XF. Switch type: Managed, Switch-laag: L2+. Console port: RJ-45/Micro-USB. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 128 Gbit/s. Netwerkstandaard: IEEE 802.11d, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae,.... Netstekker: AC-in-aansluiting. Rack-montage, Vormfactor: 1U

Beheerfuncties		Beveiliging	
Switch type *	Managed	DHCP-functies	DHCP client, DHCP relay, DHCP server
Switch-laag	L2+	Access Control List (ACL)	✓
Quality of Service (QoS)	✓	IGMP snooping	✓
Web-gebaseerd management	✓	IGMP-proxy	✓
Cloud-beheerd	✓	MAC adres filtering	✓
ARP-inspectie	✓	SSH/SSL support	✓
Locatie-instellingen (CLI) configureren	✓	Bescherming lus	✓
System event log	✓	BPDU filtering / bescherming	✓
MIB-ondersteuning	RFC1213, RFC2233, RFC1643, RFC1493, RFC2674, RFC2819, RFC2021, RFC2620, RFC2618, RFC2925	IP-MAC-Port binding	✓
Poorten & interfaces		Authenticatie	Auto VLAN, Gast-VLAN, MAC-gebaseerde authenticatie, Poortgebaseerde authenticatie
Type basis-switching RJ-45 Ethernet-poorten *	✗	Wachtwoordbeveiliging	✓
Aantal Combo SFP-poorten	4	Authenticatie type	AAA, RADIUS, TACACS+
Aantal moduleslots SPF+	4	Algoritmen wachtrijplanning	SP, WRR+SP, Weighted Round Robin (WRR)
Fibre channel-poorten	20	Multicast-functies	
Vezel-optische connector	SFP, SFP+	Multicast-ondersteuning	✓
Console port	RJ-45/Micro-USB	Multicast Listener Discovery (MLD) snooping	✓
Netstekker	AC-in-aansluiting	Protocollen	
Netwerk		Beheerprotocollen	SNMPv1/v2c/v3, SNMP
Netwerkstandaard *	IEEE 802.11d, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	GARP VLAN Registratieprotocol (GVRP)	✓
10G support *	✓	IPv4- & IPv6-functies	IPv4/IPv6 access-control list (ACL), IPv6 Telnet, IPv6 ping, IPv6 tracer
Port mirroring	✓	Design	
IP routing	✓	Rack-montage *	✓
Op beleid gebaseerde routing	✓	Vormfactor	1U
Routing entries	512	Kleur van het product	Zwart
Datastroombeheer	✓	LED-indicatoren	✓
Verbindingsaggregatie	✓	Aantal ventilatoren	1 ventilator(en)
Broadcast stormbeheer	✓	Energie	
Rate limiting	✓	Stroombron *	AC
Spanning tree protocol	✓	Vermogenstoevoer inclusief *	✓
Head-of-line (HOL) blocking	✓	Redundante voeding	✓

Netwerk		Energie	
Ethernet LAN, data-overdrachtsnelheden	10,100,1000,10000 Mbit/s	Aantal voedingen	2
Active Link-detectie	✓	Vermogensverbruik (max)	35,7 W
IPv4-routes	48	Power over Ethernet (PoE)	
IPv6-routes	48	Power over Ethernet (PoE) *	✗
VLAN=ondersteuning	✓	Eisen aan de omgeving	
Virtuele LAN-functies	Port-based VLAN, Private VLAN, Tagged VLAN, VLAN mapping, Voice VLAN	Bedrijfstemperatuur (T-T)	0 - 45 °C
Aantal VLANs	4000	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	128 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	95,23 Mpps	Warmtedissipatie	121,81 BTU/h
MAC-adrestabel *	16000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	440 mm
Statische route	✓	Diepte	220 mm
Aantal statische routes	48	Hoogte	44 mm
Jumbo Frames ondersteuning	✓	Inhoud van de verpakking	
Jumbo frames	9000	Meegeleverde kabels	AC
Packet buffergeheugen	12 MB	Gebruikershandleiding	✓
		Rekbevestigingspakket	✓



4897098688212

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.