



LevelOne FVS-3120 netwerk media converter 100 Mbit/s Single-mode Grijs

Merk : LevelOne

Artikelcode: FVS-3120

Productnaam : FVS-3120

FVS-3120

LevelOne FVS-3120 netwerk media converter 100 Mbit/s Single-mode Grijs:

HTTP Management with remote firmware upgrade supported
ICMP and ARP protocols supported
DHCP Client for easy IP address setup
LLR (Link Loss Return) supported
IEEE 802.1Q VLAN and Double VLAN (Q-in-Q) supported
Support 802.3x Flow Control to prevent lost data by controlling the device flow loading
LevelOne FVS-3120. Maximale overdrachtsnelheid van gegevens: 100 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, Converter output interface: 100Base-LX. Vezel-optische connector: SC, Connectiviteitstechnologie: Bedraad. Maximaal bereik: 20000 m, Draad modus structuur: Single-mode, Vezelkabel diameters ondersteund: 3/125,8.7/125,9/125,10/125 µm. Kleur van het product: Grijs, Land van herkomst: Taiwan, Certificering: FCC Part 15 Class A, CE. Ingangsspanning: 5 V, Stroom: 1 A, Stroomverbruik (typisch): 1,5 W



Netwerk		Design	
Maximale overdrachtsnelheid van gegevens *	100 Mbit/s	Intern *	✗
Converter input interface	10Base-T, 100Base-TX	Kleur van het product	Grijs
Converter output interface	100Base-LX	Land van herkomst	Taiwan
Netwerkstandaard	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x	Certificering	FCC Part 15 Class A, CE
Ethernet interface type	Fast Ethernet	Energie	
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Ingangsspanning	5 V
Jumbo Frames ondersteuning	✓	Stroom	1 A
Datastroombeheer	✓	Stroomverbruik (typisch)	1,5 W
Poorten & interfaces		Externe adapter	✓
Connectiviteitstechnologie	Bedraad	Gewicht en omvang	
Aantal Ethernet LAN (RJ-45)-poorten	1	Breedte	70,3 mm
Fibre channel-poorten	1	Diepte	94 mm
Vezel-optische connector *	SC	Hoogte	26,2 mm
Aansluiting voor netstroomadapter	✓	Eisen aan de omgeving	
Prestatie		Bedrijfstemperatuur (T-T)	0 - 50 °C
Maximaal bereik *	20000 m	Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Draad modus structuur	Single-mode	Verpakking	
Vezelkabel diameters ondersteund	3/125,8.7/125,9/125,10/125 µm	Breedte verpakking	160 mm
		Diepte verpakking	220 mm
		Hoogte verpakking	60 mm
		Gewicht verpakking	460 g
		Inhoud van de verpakking	
		Gebruikershandleiding	✓



4015867160183

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date