

TP-Link Omada AX1800 1800 Mbit/s Wit Power over Ethernet (PoE)

Merk : TP-Link

Productfamilie: Omada

Artikelcode: EAP613(5-PACK)

Productnaam : AX1800

TP-Link Omada AX1800. 2,4 GHz, 5 GHz, Maximale overdrachtssnelheid van gegevens: 1800 Mbit/s. Ondersteunde beveiligingsalgoritmen: HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3. Power over Ethernet (PoE). Kleur van het product: Wit



Kenmerken		Poorten & interfaces	
2,4 GHz *	✓	Aansluiting voor netstroomadapter	✓
5 GHz *	✓	Energie	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximale overdrachtssnelheid van gegevens *	1800 Mbit/s	Design	
Maximale overdrachtssnelheid van gegevens (2.4 GHz)	574 Mbit/s	Plaatsing *	Plafond, Muur
Maximale overdrachtssnelheid van gegevens (5 GHz)	1201 Mbit/s	Kleur van het product *	Wit
Frequentieband	2.4 - 5 GHz	Reset button	✓
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	LED-indicatoren	✓
Automatische kanaalselectie	✓	Antenne	
Automatisch scannen kanalen	✓	Soort antenne *	Intern
MIMO	✓	Type antennerichting	Omni-directioneel
MIMO-type	Multi User MIMO	Antennas quantity	4
Spread spectrum methode	OFDMA	Antenne versterkingsniveau (max)	5 dBi
Virtuele LAN-functies	SSID-based VLAN assignment	Prestatie	
Rate limiting	✓	Compatibele besturingssystemen	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Adaptieve bandbreedtebeheer	✓	Certificaten	
Bandbreedteaansturing	✓	Certificering	CE, FCC, RoHS
Airtime Fairness (ATF)	✓	Gewicht en omvang	
Zendvermogen (CE)	<20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz band1/2, EIRP); <25 dBm (5 GHz band3)	Breedte	160 mm
Zendvermogen (FCC)	<25 dBm (2.4 GHz); <25 dBm (5 GHz)	Diepte	160 mm
		Hoogte	33,6 mm
		Inhoud van de verpakking	
		Aantal per verpakking	5 stuk(s)
		Montage gereedschap	✓

Beveiliging		Inhoud van de verpakking	
Ondersteunde beveiligingsalgoritmen *	HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3	Snelstartgids	✓
Aantal SSID-ondersteuningen	16	Eisen aan de omgeving	
Beheerfuncties		Relatieve vochtigheid in bedrijf (V-V)	0 - 40 procent
Web-gebaseerd management	✓	Bedrijfstemperatuur (T-T)	10 - 90 °C
Beheerplatform	Omada	Temperatuur bij opslag	-40 - 70 °C
Poorten & interfaces		Luchtvochtigheid bij opslag	5 - 90 procent
Aantal Ethernet LAN (RJ-45)-poorten *	1		



4895252500523



0840030704314



840030704314

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.