

## ASUS PN52-BBR758HD Zwart 5800H 3,2 GHz

**Merk :** ASUS

**Artikelcode:** 90MR00R2-M000E0

**Productnaam :** PN52-BBR758HD



ASUS PN52-BBR758HD. Type product: Mini PC barebone. Ondersteunde geheugen types: DDR4-SDRAM, Aantal geheugenslots: 2, Maximum intern geheugen: 32 GB. Ondersteunde types opslag-drives: HDD & SSD, Opslag schijf-interface: PCI Express. Aantal Ethernet LAN (RJ-45)-poorten: 1. Wi-Fi-standaarden: Wi-Fi 6E (802.11ax), Bluetooth-versie: 5.2. Netvoeding: 120 W



Processor		Netwerk	
Processorfabrikant	AMD	Bluetooth	✓
Processorfamilie	AMD Ryzen™ 7	Bluetooth-versie	5.2
Processormodel	5800H	Poorten & interfaces	
Aantal processorkernen	8	Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type A *	4
Processor aantal threads	16	Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type C	1
Maximale turbofrequentie van processor	4,4 GHz	Aantal poorten USB 3.2 Gen 2 (3.1 Gen 2) Type A	1
Frequentie van processor	3,2 GHz	Aantal poorten USB 3.2 Gen 2 (3.1 Gen 2) Type C	1
Type processor *	✓	Aantal HDMI-poorten *	2
Processor cache	16 MB	HDMI versie	2.1
Geïnstalleerde processorcache	4 MB	Aantal DisplayPorts	1
L3 cache	16 MB	DisplayPort versie	1.4
Thermal Design Power (TDP)	45 W	Combo koptelefoon/microfoon port	✓
Geheugen		Aantal Ethernet LAN (RJ-45)-poorten *	1
Aantal geheugenslots *	2	Aansluiting voor netstroomadapter	✓
Maximum intern geheugen	32 GB	Design	
Supported memory clock speeds	3200 MHz	Kleur van het product *	Zwart
Ondersteunde geheugen types	DDR4-SDRAM	Type product *	Mini PC barebone
Opslagmedia		Prestatie	
Ondersteunde types opslag-drives *	HDD & SSD	Trusted Platform Module (TPM)	✓
Opslagschijf afmetingen ondersteund *	M.2	Certificaten	
SSD-vormfactor	M.2	Certificering	BSMI/CB/CE/FCC/UL/CCC/Energy Star/C-Tick/WiFi/RF/VCCI
Opslag schijf-interface	PCI Express	Software	
Aantal storage drives ondersteund	3	Inclusief besturingssysteem	✗
Grafisch		Energie	
Ingebouwde grafische adapter *	✓	Soort voeding *	Externe AC-adapter
Grafische adapter-familie	AMD	Netvoeding	120 W
On-board graphics adapter model	AMD Radeon Graphics	AC-adapter, uitgangsspanning	19 V
Audio		AC-adapter, uitgangsstroom	6,32 A
Ingebouwde luidsprekers *	✗	Gewicht en omvang	
Netwerk		Breedte	120 mm
Wifi-standaard	Wi-Fi 6E (802.11ax)	Diepte	130 mm
Wi-Fi-standaarden	Wi-Fi 6E (802.11ax)	Hoogte	58 mm
Ethernet LAN *	✓		
Wifi *	✓		
LAN controller	Realtek RTL8125B-CG		

**Gewicht en omvang**

Gewicht

1 kg



4711081798972



0195553798976



195553798976

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.