



## ACT 10G Ethernet Media Converter

Merk : ACT

Artikelcode: AC4455

Productnaam : 10G Ethernet Media Converter

- 10G Media Converter voor het omzetten van Gigabit ethernet over glasvezel naar Gigabit ethernet over koper (RJ45)
  - Zet Gigabit ethernet over koper (RJ45) om naar Gigabit ethernet over glasvezel
  - Geschikt voor een singlemode of multimode Uncoded SFP+ transceiver
  - Link Fault Passthrough (LFP) ondersteuning
  - Auto-negotiation functie
  - Compacte metalen behuizing
- 10G Ethernet Media Converter



### ACT 10G Ethernet Media Converter:

De AC4455 10G Ethernet Media Converter biedt een flexibele en hoogwaardige oplossing voor het maken van een snelle en eenvoudige overgang van Gigabit ethernet over glasvezel naar Gigabit ethernet over koper (RJ45) en vice versa. Deze unmanaged media converter heeft een open SFP+ slot voor een singlemode of multimode uncoded SFP+ module. Daarnaast heeft de ethernet media converter Link Fault Passthrough (LFP) voor het detecteren van fouten in de link/verbinding. De media converter heeft diverse werkmodi die worden ingesteld via de dip-switches.



Netwerk		Prestatie	
Maximale overdrachtsnelheid van gegevens *	10000 Mbit/s	Draad modus structuur	Multimode, Single-mode
Converter output interface	10GBASE-R	<b>Design</b>	
Netwerkstandaard	IEEE 802.3ab	Intern *	✗
Ethernet interface type	2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Gigabit Ethernet	LED-indicatoren	Activiteit, Link, Stroom, Snelheid
Ethernet LAN, data-overdrachtsnelheden	1000,2500,5000,10000 Mbit/s	Kleur van het product	Zwart
Fiber ethernet cabling technologie	10GBASE-R	Materiaal behuizing	Metaal
Auto-negotiation	✓	<b>Energie</b>	
Link Fault Pass-through (LFP)	✓	Ingangsspanning	12 V
<b>Poorten &amp; interfaces</b>		Stroom	1 A
Connectiviteitstechnologie	Bedraad	Externe adapter	✓
Aantal Ethernet LAN (RJ-45)-poorten	1	<b>Gewicht en omvang</b>	
Fibre channel-poorten	1	Breedte	70 mm
Vezel-optische connector *	SFP+	Diepte	98 mm
Aansluiting voor netstroomadapter	✓	Hoogte	26 mm
		Gewicht	205 g
		<b>Eisen aan de omgeving</b>	
		Bedrijfstemperatuur (T-T)	0 - 60 °C
		Temperatuur bij opslag	-20 - 70 °C
		<b>Verpakking</b>	
		Type verpakking	Doos
		<b>Inhoud van de verpakking</b>	
		Inclusief AC-adapter	✓



8716065517903

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date