



## LevelOne GEU-0522 netwerk-switch Gigabit Ethernet (10/100/1000) Zwart

**Merk :** LevelOne

**Artikelcode:** GEU-0522

**Productnaam :** GEU-0522

LevelOne GEU-0522. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. Full duplex. MAC-adrestabel: 1000 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u



Poorten & interfaces		Power over Ethernet (PoE)	
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Power over Ethernet (PoE) *	✗
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	<b>Eisen aan de omgeving</b>	
<b>Netwerk</b>		Bedrijfstemperatuur (T-T)	0 - 50 °C
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u	Temperatuur bij opslag	-40 - 70 °C
10G support *	✗	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-T, 1000BASE-T	Luchtvochtigheid bij opslag	5 - 90 procent
Full duplex	✓	<b>Gewicht en omvang</b>	
Auto MDI/MDI-X	✓	Breedte	86 mm
Auto-negotiation	✓	Diepte	23 mm
MAC-adres zelflerende functie	✓	Hoogte	89 mm
MAC-adres zelfverouderende functie	✓	Gewicht	71,4 g
<b>Data-uitwisseling</b>		<b>Inhoud van de verpakking</b>	
Switchingcapaciteit *	10 Gbit/s	Snelstartgids	✓
MAC-adrestabel *	1000 entries	<b>Verpakking</b>	
Store-and-forward	✓	Inclusief AC-adapter	✓
Jumbo Frames ondersteuning	✓	Type verpakking	Doos
Jumbo frames	9000	Breedte verpakking	95 mm
Packet forwarding rate (1 Gbps)	1488100 pps	Diepte verpakking	82 mm
Packet forwarding rate (100 Mbps)	148810 pps	Hoogte verpakking	98 mm
Packet forwarding rate (10 Mbps)	14880 pps	Gewicht verpakking	184 g
<b>Design</b>		<b>Certificaten</b>	
Stapelbaar *	✗	Certificering	CE, FCC
Kleur van het product	Zwart	<b>Logistieke gegevens</b>	
LED-indicatoren	Activiteit, Link, Stroom	Land van herkomst	China
<b>Prestatie</b>		(Buitenste) hoofdverpakking breedte	495 mm
Buffergrootte	64 KB	(Buitenste) hoofdverpakking lengte	191 mm
<b>Energie</b>		(Buitenste) hoofdverpakking hoogte	516 mm
Stroom	0.6 A	Code geharmoniseerd systeem (HS)	85176990
Ingangsspanning	5 V	(Buitenste) hoofdverpakking brutogewicht	10,2 kg
		Hoeveelheid per (buitenste) hoofdverpakking	50 stuk(s)



4015867202500



4015867229958



0846359048078



846359048078

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.