

NETGEAR MS108UP Unmanaged 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE)

Merk : NETGEAR

Artikelcode: MS108UP-100EUS

Productnaam : MS108UP



NETGEAR MS108UP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: 2.5G Ethernet (100/1000/2500), Aantal basis-switching RJ-45 Ethernet-poorten: 8. Full duplex. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 40 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt,.... DC voltage input: 54 V. Power over Ethernet (PoE). Ophangstelsysteem voor aan de muur

Beheerfuncties		Design	
Switch type *	Unmanaged	Ophangstelsysteem voor aan de muur	✓
Quality of Service (QoS)	✓	Elektromagnetische compatibiliteit	CE, FCC part 15 Class B, ISED, VCCI, KC, CCC, BSMI, RCM
Poorten & interfaces		Certificering	CB, CSA, CCC, BSMI, RCM
Aantal basis-switching RJ-45 Ethernet-poorten *	8	Prestatie	
Type basis-switching RJ-45 Ethernet-poorten *	2.5G Ethernet (100/1000/2500)	Fanloos	✓
Aantal 2.5G Ethernet (koper)poorten	8	Mean time between failures (MTBF)	373643,7 uur
Netwerk		Energie	
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x	Stroombron *	DC
10G support *	✗	Vermogenstoevoer inclusief *	✓
Full duplex	✓	DC voltage input	54 V
Half-duplex	✓	Stroom	4.7 A
Auto MDI/MDI-X	✓	Power over Ethernet (PoE)	
Head-of-line (HOL) blocking	✓	Power over Ethernet (PoE) *	✓
Ethernet LAN, data-overdrachtsnelheden	100,1000,2500 Mbit/s	Aantal Power over Ethernet plus (PoE +)-poorten	8
Auto-sensing	✓	Totaal Power over Ethernet (PoE)-budget	230 W
VLAN=ondersteuning	✓	Eisen aan de omgeving	
Aantal VLANs	64	Bedrijfstemperatuur (T-T)	0 - 40 °C
Data-uitwisseling		Temperatuur bij opslag	-20 - 70 °C
Switchingcapaciteit *	40 Gbit/s	Relatieve vochtigheid in bedrijf (V-V)	0 - 90 procent
MAC-adrestabel *	16000 entries	Hoogte, in bedrijf	0 - 3000 m
Latentie (1 Gbps)	3,593 µs	Warmtedissipatie	923,49 BTU/h
Jumbo Frames ondersteuning	✓	Gewicht en omvang	
Jumbo frames	12000	Breedte	210 mm
Packet forwarding rate (1 Gbps)	1488000 pps	Diepte	140 mm
Packet buffergeheugen	1,5 MB	Hoogte	40 mm
Design		Gewicht	900 g
Rack-montage *	✗	Logistieke gegevens	
Materiaal behuizing	Metaal	Code geharmoniseerd systeem (HS)	85176990
LED-indicatoren	Activiteit, Link, Power over Ethernet (PoE), Stroom		



0606449156874



606449156874

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.