

Delock External Enclosure mSATA > Multiport USB 3.0 + eSATAp

Description

This small aluminium-enclosure by Delock enables you to install a mSATA SSD and provides up to 4 different connecting options due to its special Multiport USB 3.0 + eSATAp interface. The Multiport is a combination of eSATA and USB 3.0 interface, which supports a fast data transfer and a voltage supply of up to 5 V. For extra voltage supply, when connecting via eSATA, you will find an additional power cable included in delivery.

Connecting options:

1. USB 3.0 (power via USB)
2. USB 2.0 (power via USB)
3. eSATAp (Power Over eSATA combo-connection eSATA+USB - eSATA for data and USB for power)
4. eSATA (eSATA for data and power via included USB power cable)



Specification

- External aluminium-enclosure for mSATA 1.5 Gb/s, 3 Gb/s and 6 Gb/s SSD with half size or full size
- Only support Intel mSATA pin definition, does not support ASUS Eee PC SSD card
- Connector
 - external: 1 x Multiport USB 3.0 + eSATAp
 - 1 x DC for power when connecting via eSATA
 - internal: 1 x mSATA slot (half size / full size)
- Dimension DC connector:
 - Length of pin: 9.5 mm
 - ø 3.5 / 1.3 mm
 - Polarity: ground outside, plus inside
- Data transfer rate:
 - USB 3.0 up to 5 Gb/s
 - USB 2.0 up to 480 Mb/s
 - eSATA up to 6 Gb/s
- Enclosure with full-PCB
- LED indicator for power and access
- Dimension (LxWxH): 82.5 mm x 60 mm x 12 mm
- Hot Swap, Plug & Play

Item No. 42508



EAN	4043619425082
Country of origin	Taiwan, Republic of China

System requirements

- Windows Vista/7/8, Mac 10.7, Linux Mint
- PC or notebook with
 1. a free USB 3.0 port
 2. or a free USB 2.0 port
 3. or a free eSATAp port
 4. or o free eSATA port and a free USB port for power

Package content

- Externes Gehäuse mSATA
- USB 3.0-A/A Kabel
- DC-USB Stromkabel
- eSATAp Kabel
- Tasche, Schraubendreher, Schrauben
- Bedienungsanleitung

Package

- Retail Box

Images

