

TP-Link TL-SG105PP-M2 network-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : TP-Link

Artikelcode: TL-SG105PP-M2

Productnaam : TL-SG105PP-M2

TP-Link TL-SG105PP-M2. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 25 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE)



Beheerfuncties		Prestatie	
Switch type *	Unmanaged	Fanloos	✓
Quality of Service (QoS)	✓	Energie	
Poorten & interfaces		Stroombron *	DC/PoE
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Vermogenstoevoer inclusief *	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Aantal voedingen	1
Aantal 2.5G Ethernet (koper)poorten	5	AC-ingangsspanning	220 V
Netwerk		AC-ingangsfrequentie	50 Hz
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Stroom	2.43 A
10G support *	✗	Ingangsspanning	53.5 V
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Vermogensverbruik (max)	143,37 W
Ondersteundende kabel types	Cat3, Cat4, Cat5, Cat5e	Power over Ethernet (PoE)	
Datastroombeheer	✓	Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Aantal Power over Ethernet 4PPoE (PoE++)-poorten	4
Auto-negotiation	✓	Vermogen per poort Power over Ethernet (PoE)	60 W
MAC-adres zelflerende functie	✓	Totaal Power over Ethernet (PoE)-budget	123 W
MAC-adres zelfverouderende functie	✓	Eisen aan de omgeving	
Data-uitwisseling		Bedrijfstemperatuur (T-T)	0 - 40 °C
Switchingcapaciteit *	25 Gbit/s	Temperatuur bij opslag	-40 - 70 °C
Verzending snelheid	18,6 Mpps	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
MAC-adrestabel *	4000 entries	Luchtvochtigheid bij opslag	5 - 90 procent
Store-and-forward	✓	Warmtedissipatie	488,89 BTU/h
		Gewicht en omvang	
		Breedte	209 mm
		Diepte	126 mm

Beveiliging		Gewicht en omvang	
IGMP snooping	✓	Hoogte	26 mm
Design		Inhoud van de verpakking	
Rack-montage *	✗	Meegeleverde kabels	AC
Kleur van het product	Zwart	Gebruiksaanwijzing	✓
Materiaal behuizing	Staal	Verpakking	
LED-indicatoren	✓	Type verpakking	Doos
		Certificaten	
		Certificering	CE, FCC, RoHS



4895252501148



4895252501131

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.