



APC Smart-UPS Li-ion SMTL2200RMI2UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA

Merk : APC

Artikelcode: SMTL2200RMI2UC

Productnaam : APC Smart-UPS Li-ion SMTL2200RMI2UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA



APC Smart-UPS Li-ion SMTL2200RMI2UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA
APC Smart-UPS Li-ion SMTL2200RMI2UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA. UPS-topologie: Line-interactive, Output power capacity: 2,2 kVA, Uitgangsvermogen: 1980 W. Stopcontacttypes: C13 stekker, C19 stekker, Aantal AC uitgangen: 10 AC-uitgang(en), Soort serieële aansluiting: RJ-45. Batterijtechnologie: Sealed Lead Acid (VRLA), Acculevensduur (max): 5 jaar, Accu/Batterij oplaadtijd: 3 uur. Vormfactor: Rackmontage/toren, Kleur van het product: Zwart, Grijs, Rackcapaciteit: 2U. Certificaten van naleving: CE, GS mark, RoHS, VDE, Certificering: IRAM, RCM



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	2.2 kVA	Automatic battery test	✓
Output power *	1980 W	Cold start	✓
Waveform *	Sine	Design	
Input operation voltage (min) *	151 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	302 V	Rack capacity	2U
Input frequency *	50/60 Hz	Cable length	2 m
Output operation voltage (min)	220 V	Product colour *	Black, Grey
Output operation voltage (max)	240 V	Display type	LCD
Output frequency	50/60 Hz	LED indicators	✓
Automatic Voltage Regulation (AVR)	✓	Operational conditions	
Surge energy rating	375 J	Operating temperature (T-T)	0 - 40 °C
Response time	6 ms	Storage temperature (T-T)	-15 - 45 °C
Heat dissipation	215 BTU/h	Operating relative humidity (H-H)	0 - 95%
Number of input phases	1	Storage relative humidity (H-H)	0 - 95%
Number of output phases	1	Operating altitude	0 - 3048 m
Output voltage Total Harmonic Distortion (THD)	5%	Non-operating altitude	0 - 15240 m
Noise level	55 dB	Certificates	
Audible alarm(s)	✓	Compliance certificates	CE, GS mark, RoHS, VDE
Auto-restart	✓	Certification	IRAM, RCM
Power source type	AC	Packaging content	
Ports & interfaces		Rack mount kit	✓
AC outlet types	C13 coupler, C19 coupler	Cables included	USB cable
AC outlets quantity	10 AC outlet(s)	Sustainability	
Number of output IEC jumpers	3	Sustainability compliance	✓
USB port	✓		
Serial interface	✓		

Ports & interfaces		Weight & dimensions	
Serial interface type	RJ-45	Width	432 mm
Ethernet LAN (RJ-45) ports	1	Depth	683 mm
SmartSlot	✓	Height	86 mm
Battery		Weight	42.3 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Battery life (max)	5 year(s)	Package width	980 mm
Battery recharge time	3 h	Package depth	600 mm
		Package height	254 mm
		Package weight	49.7 kg
Other features			
		Input connection type	BS1363A British, IEC 320 C20, Schuko CEE 7 / EU1-16P
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304643197



731304643197

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2025. Prints or copies of Information are only valid on the printed Publication date