
ZYXEL

Zyxel WBE660S-EU0101F Wifi 7 draadloos toegangspunt (WAP) 11530 Mbit/s Grijs (PoE)

Merk: Zyxel Artikelcode: WBE660S-EU0101F

Productnaam : WBE660S-EU0101F Wifi 7 draadloos toegangspunt (WAP) 11530 Mbit/s Grijs (PoE)







2.4 GHz*				
Fig. 6 GHz *	Features		Design	
LED indicators Variable Variable LED indicators Variable Variable LED indicators Variable Variable LED indicators Variable Varia	2.4 GHz *	1	Placement *	Wall
Maximum data transfer rate (2.4 1376 Mbit/s 1376 Mbit/s Antenna type * Internal Maximum data transfer rate (2.4 1376 Mbit/s 442) Maximum data transfer rate (5 GHz) 8646 Mbit/s Weight & dimensions Maximum data transfer rate (6 GHz) 11530 Mbit/s Width 310 mm Ethernet LAN data rates 10,100,1000,2500,5000,10000 Mbit/s Height 56 mm Metworking standards IEEE 802.11a, IEEE 802.11a, IEEE 802.11a, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11a, IEEE 802.11b, IEEE 802.11b	5 GHz *	✓	Product colour *	Grey
Maximum data transfer rate (2.4 1376 Mbit/s 3Hz) Maximum data transfer rate (5 GHz) 8646 Mbit/s Weight & dimensions Maximum data transfer rate (6 GHz) 11530 Mbit/s Width 310 mm Ethernet LAN data rates 10,100,1000,2500,5000,10000 Mbit/s Depth 178 mm Methernet LAN data rates 10,100,1000,2500,5000,10000 Mbit/s Socially, IEEE 802.11ac, IEEE 802.11ac, IEEE 802.11b,	6 GHz *	✓	LED indicators	✓
Maximum data transfer rate (5 GHz) 8646 Mbit/s Weight & dimensions Maximum data transfer rate (6 GHz) 11530 Mbit/s Width 310 mm 10,100,1000,2500,5000,10000 Depth 178 mm Mbit/s Height 56 mm IEEE 802.11a, IEEE 802.1a, III	Maximum data transfer rate *	11530 Mbit/s	Antenna	
Maximum data transfer rate (6 GHz) 11530 Mbit/s Width 310 mm Ethernet LAN data rates 10,100,1000,2500,5000,10000 Mbit/s Height 56 mm Networking standards 10,100,110,1000,2500,5000,10000 Mbit/s Height 56 mm Networking standards 10,100,110,110,110,110,110,110,110,110,	Maximum data transfer rate (2.4 GHz)	1376 Mbit/s	Antenna type *	Internal
Ethernet LAN data rates 10,100,1000,2500,5000,10000 Mbit/s Height 56 mm IEEE 802.11a, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11b, IEEE 802.11c, IEEE 802.11b, IEEE 802.11c, IEEE 802.11b, IEEE 802.11b, IEEE 802.11c, IEEE 802.11	Maximum data transfer rate (5 GHz)	8646 Mbit/s	Weight & dimensions	
Mbit/s Networking standards NETHORNOOR Molitys Networking standards NETHORNOOR Molitys Networking standards NETHORNOOR Molitys NETHORNOOR MOLITY NETHORNOOR MOLI	Maximum data transfer rate (6 GHz)	11530 Mbit/s	Width	310 mm
Networking standards Neight Networking data Networking standards Neight Networking data Networking standards Neight Networking data Networking data Neight Neight	Ethernet LAN data rates		•	
Networking standards 802.11ax, IEEE 802.11b, IEEE 802.11n Packaging data Package width Package depth Package height Package weight Packaging content Quantity per pack Packaging content Operational conditions Operating relative humidity (H-H) Operating temperature (T-T) Package relative humidity (H-H) Package relative humidity (H-H) Package weight Packaging content Operating relative humidity (H-H) Package weight Packaging content Operating relative humidity (H-H) Package weight Packag			•	
802.11g, IEEE 802.11n Wi-Fi Multimedia (WMM)/(WME) VLAN support VLAN	Networking standards	802.11ax, IEEE 802.11b, IEEE	Weight	1.41 kg
ALAN support AL	3		Packaging data	
Package height Package weight 2.04 kg Package weight	Wi-Fi Multimedia (WMM)/(WME)	✓	Package width	377 mm
Package weight 2.04 kg Packaging content MAC address filtering Management features Firmware upgradeable Ports & interfaces Covert LAN (RJ-45) ports * 2 Covert over Ethernet (PoE) * Covert over the covert ethernet (PoE) * Covert over Ethe	VLAN support	✓	Package depth	231 mm
Package weight 2.04 kg Packaging content Quantity per pack 1 pc(s) Packaging content Quantity per pack 0 perational conditions Operating relative humidity (H-H) 10 - 90% Operating temperature (T-T) 0 - 45 °C Storage temperature (T-T) -40 - 70 °C Storage relative humidity (H-H) 10 - 90% Packaging content Quantity per pack 1 pc(s) Operating relative humidity (H-H) 10 - 90% Operating temperature (T-T) -40 - 70 °C Storage relative humidity (H-H) 10 - 90% Packaging content Quantity per pack 1 pc(s)	Security			
MAC address filtering Management features Firmware upgradeable Ports & interfaces Ethernet LAN (RJ-45) ports * 2 Power Power over Ethernet (PoE) * Power over Ethernet (PoE) * Poc voltage range Packaging content Quantity per pack Departing temperature Operating temperature (T-T) Operating temp	•	WFP. WPA. WPA2-PSK. WPA3	Package weight	2.04 kg
Management features Firmware upgradeable Ports & interfaces Cethernet LAN (RJ-45) ports * 2 Cover over Ethernet (PoE) * Cover over Ethernet (PoE) * Cover over Storage temperature (PoE) * Cover over Storage temperature (PoE) * Cover over Ethernet (PoE) * Cover over Et	MAC address filtering		Packaging content	
Operational conditions Operating relative humidity (H-H) 10 - 90% Operating temperature (T-T) 0 - 45 ° C Operating temperature (T-T) - 40 - 70 ° C Operating temperature (T-T) 10 - 90% Operating temperature (T-T) - 40 - 70 ° C Operating tem	Management features		Quantity per pack	1 pc(s)
Operating relative humidity (H-H) 10 - 90% Operating temperature (T-T) 0 - 45 °C Storage temperature (T-T) -40 - 70 °C Storage relative humidity (H-H) 10 - 90% Operating temperature (T-T) -40 - 70 °C Storage relative humidity (H-H) 10 - 90% Over over Ethernet (PoE) * OC voltage range 15 V		1	Operational conditions	
Storage relative humidity (H-H) Power over Ethernet (PoE) * OC voltage range Operating temperature (T-T) Storage temperature (T-T) -40 - 70 °C Storage relative humidity (H-H) 10 - 90%	. 5	•	Operating relative humidity (H-H)	10 - 90%
Power Over Ethernet (PoE) * ✓ CO voltage range 15 V	Ports & interfaces		Operating temperature (T-T)	0 - 45 °C
Power over Ethernet (PoE) * ✓ DC voltage range 15 V	Ethernet LAN (RJ-45) ports *	2	Storage temperature (T-T)	-40 - 70 °C
DC voltage range 15 V	Power		Storage relative humidity (H-H)	10 - 90%
	Power over Ethernet (PoE) *	1		
nput current 3 A	DC voltage range	15 V		
	Input current	3 A		



4718937631193

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.