

Zyxel XMG1915-18EP Managed L2 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE)



Merk : Zyxel

Artikelcode: XMG1915-18EP-EU0101F

Productnaam : XMG1915-18EP

Zyxel XMG1915-18EP. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: 2.5G Ethernet (100/1000/2500), Aantal basis-switching RJ-45 Ethernet-poorten: 16. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 120 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3bz,.... Power over Ethernet (PoE). Rack-montage

Beheerfuncties		Design	
Switch type *	Managed	Rack-montage *	✓
Switch-laag	L2	LED-indicatoren	✓
Quality of Service (QoS)	✓	Prestatie	
Poorten & interfaces		Intern geheugen	256 MB
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Flash memory	32 MB
Type basis-switching RJ-45 Ethernet-poorten *	2.5G Ethernet (100/1000/2500)	Upgraden van firmware mogelijk	✓
Aantal moduleslots SPF+	2	Mean time between failures (MTBF)	954,032 uur
Netwerk		Energie	
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3x, IEEE 802.3z	Stroombron *	AC/PoE
		Vermogenstoevoer inclusief *	✓
10G support *	✓	AC-ingangsspanning	100 - 240 V
VLAN=ondersteuning	✓	AC-ingangsfrequentie	50/60 Hz
Virtuele LAN-functies	MAC address-based VLAN, Port-based VLAN, Voice VLAN	Vermogensverbruik (max)	230,81 W
Data-uitwisseling		Power over Ethernet (PoE)	
Switchingcapaciteit *	120 Gbit/s	Power over Ethernet (PoE) *	✓
Verzending snelheid	89,2 Mpps	Hoeveelheid Power over Ethernet (PoE) ports	8
MAC-adrestabel *	16000 entries	Totaal Power over Ethernet (PoE)-budget	180 W
Jumbo Frames ondersteuning	✓	Eisen aan de omgeving	
Jumbo frames	12000	Bedrijfstemperatuur (T-T)	0 - 40 °C
Packet buffergeheugen	1,5 MB	Temperatuur bij opslag	-40 - 70 °C
Beveiliging		Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
DHCP-functies	DHCP client, DHCP relay, DHCP snooping	Luchtvochtigheid bij opslag	5 - 95 procent
IGMP snooping	✓	Gewicht en omvang	
Ondersteunde beveiligingsalgoritmen	SNMP, SNMPv2, SNMPv3	Breedte	330 mm
MAC adres filtering	✓	Diepte	230 mm
SSH/SSL support	✓	Hoogte	44 mm
Authenticatie type	RADIUS	Gewicht	2,6 kg
Multicast-functies		Verpakking	
Multicast-ondersteuning	✓	Meegeleverde kabels	AC
Multicast-functies	Multicast-doorsturen		



4718937631490



0760559130329



760559130329

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-SEP-2024. Prints or copies of Information are only valid on the printed Publication date