



## TP-Link TL-SG1006PP netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs



**Merk :** TP-Link

**Artikelcode:** TL-SG1006PP

**Productnaam :** TL-SG1006PP

TP-Link TL-SG1006PP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 6. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 12 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC voltage input: 53.5 V. Power over Ethernet (PoE). Rack-montage

Beheerfuncties		Design	
Switch type *	Unmanaged	Kleur van het product	Grijs
Quality of Service (QoS)	✓	LED-indicatoren	✓
<b>Poorten &amp; interfaces</b>		Certificering	FCC, CE, RoHS
Aantal basis-switching RJ-45 Ethernet-poorten *	6	<b>Prestatie</b>	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Fanloos	✓
<b>Netwerk</b>		<b>Energie</b>	
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Stroombron *	DC/PoE
10G support *	✗	Vermogenstoever inclusief *	✓
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	DC voltage input	53.5 V
Ondersteundende kabel types	Cat3, Cat4, Cat5, Cat5e, Cat6	Stroom	1.31 A
Datastroombeheer	✓	Stroomverbruik (typisch)	4,75 W
Auto MDI/MDI-X	✓	Vermogensverbruik (max)	71,46 W
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	<b>Power over Ethernet (PoE)</b>	
Auto-negotiation	✓	Power over Ethernet (PoE) *	✓
MAC-adres zelflerende functie	✓	Hoeveelheid Power over Ethernet (PoE) ports	4
MAC-adres zelfverouderende functie	✓	Totaal Power over Ethernet (PoE)-budget	64 W
<b>Data-uitwisseling</b>		<b>Eisen aan de omgeving</b>	
Switchingcapaciteit *	12 Gbit/s	Bedrijfstemperatuur (T-T)	0 - 40 °C
Verzending snelheid	8,928 Mpps	Temperatuur bij opslag	-40 - 70 °C
MAC-adrestabel *	4000 entries	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Store-and-forward	✓	Luchtvochtigheid bij opslag	5 - 90 procent
<b>Beveiliging</b>		Warmtedissipatie	16,2 BTU/h
IGMP snooping	✓	<b>Gewicht en omvang</b>	
<b>Design</b>		Breedte	158 mm
Rack-montage *	✓	Diepte	101 mm
Stapelbaar *	✓	Hoogte	25 mm
		<b>Verpakking</b>	
		Snelstartgids	✓
		Type verpakking	Doos



4895252500332



4895252500325

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.