



TP-Link TL-SG1210PP netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : TP-Link

Artikelcode: TL-SG1210PP

Productnaam : TL-SG1210PP

TP-Link TL-SG1210PP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 10. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 20 Gbit/s. Netwerkstandaard: IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Power over Ethernet (PoE)



Beheerfuncties		Prestatie	
Switch type *	Unmanaged	Fanloos	✓
Quality of Service (QoS)	✓	Energie	
Poorten & interfaces		Stroombron *	DC/PoE
Aantal basis-switching RJ-45 Ethernet-poorten *	10	Vermogenstoevoer inclusief *	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Aantal voedingen	1
Aantal Gigabit Ethernet (koper)-poorten	10	AC-ingangsspanning	90 - 220 V
Aantal Combo SFP-poorten	1	AC-ingangsfrequentie	50 Hz
Netwerk		Stroom	2.43 A
Netwerkstandaard *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Ingangsspanning	53.5 V
10G support *	✗	Vermogensverbruik (max)	144,1 W
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX	Power over Ethernet (PoE)	
Ondersteundende kabel types	Cat3, Cat4, Cat5, Cat5e	Power over Ethernet (PoE) *	✓
Datastroombeheer	✓	Aantal Power over Ethernet plus (PoE +)-poorten	2
Auto MDI/MDI-X	✓	Aantal Power over Ethernet 4PPoE (PoE++)-poorten	6
Auto-negotiation	✓	Totaal Power over Ethernet (PoE)-budget	123 W
MAC-adres zelflerende functie	✓	Eisen aan de omgeving	
MAC-adres zelfverouderende functie	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Data-uitwisseling		Temperatuur bij opslag	-40 - 70 °C
Switchingcapaciteit *	20 Gbit/s	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Verzending snelheid	14,88 Mpps	Luchtvochtigheid bij opslag	5 - 90 procent
MAC-adrestabel *	4000 entries	Warmtedissipatie	482,17 BTU/h
Store-and-forward	✓	Gewicht en omvang	
Beveiliging		Breedte	209 mm
IGMP snooping	✓	Diepte	126 mm
Design		Hoogte	26 mm
Rack-montage *	✗	Verpakking	
		Meegeleverde kabels	AC

Design		Verpakking	
Kleur van het product	Zwart	Gebruiksaanwijzing	✓
Materiaal behuizing	Staal	Type verpakking	Doos
LED-indicatoren	✓	Logistieke gegevens	
Certificering	FCC, CE, RoHS	Code geharmoniseerd systeem (HS) 85176990	



4895252500356



4895252500349

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-SEP-2024. Prints or copies of Information are only valid on the printed Publication date