



TP-Link VIGI C340S Kogel (vorm) IP-beveiligingscamera Buiten 2688 x 1520 Pixels Muur

Merk : TP-Link

Productfamilie: VIGI

Artikelcode: VIGI-C340S-4MM

Productnaam : VIGI C340S



TP-Link VIGI C340S. Soort: IP-beveiligingscamera, Ondersteuning voor plaatsing: Buiten, Connectiviteitstechnologie: Bedraad. Montagewijze: Muur, Kleur van het product: Wit, Vormfactor: Kogel (vorm). Minimale belichting: 0,0005 Lux, Kijkhoek lens, horizontaal: 95.2°, Kijkhoek lens, verticaal: 50.6°. Type beeldsensor: CMOS, Omvang optische sensor: 25,4 / 1,8 mm (1 / 1.8"). Detectieafstand: 70 m, Observatieafstand: 29 m, Herkenningsafstand: 14 m

Performance		Video	
Type *	IP security camera	Maximum resolution *	2688 x 1520 pixels
Placement supported *	Outdoor	Total megapixels *	4 MP
Connectivity technology *	Wired	Video compression formats	H.264, H.264+, H.265, H.265+
Wide Dynamic Range (WDR)	✓	Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2550 x 1440, 2688 x 1520
Day/night mode	✓	Frame rate	60 fps
Luminous flux	0.0005 lm	Noise reduction	✓
Dynamic range	120 dB	Noise reduction technology	3D noise reduction
Design		Privacy masking	✓
Form factor *	Bullet	Bit rate	4 Mbps
Mounting type *	Wall	Region of Interest (ROI) encoding	✓
Product colour *	White	Audio	
Housing material	Metal, Plastic	Built-in speaker(s)	✓
International Protection (IP) code	IP67	Sample rate	8 kHz
Camera		Signal-to-Noise Ratio (SNR)	52 dB
Minimum illumination	0.0005 lx	Built-in microphone	✓
Lens viewing angle, horizontal	95.2°	Bit rate range	64 - 64 Kbit/s
Lens viewing angle, vertical	50.6°	Network	
Lens viewing angle, diagonal	114.7°	Ethernet LAN *	✓
Tilt angle range	-90 - 90°	Ethernet interface type	Fast Ethernet
Pan range	-90 - 90°	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS
Camera shutter speed	1/10000 s	Ports & interfaces	
Number of Privacy masking areas	4	Ethernet LAN (RJ-45) ports	1
Image sensor			
Optical sensor size	25.4 / 1.8 mm (1 / 1.8")		
Progressive scan	✓		
Sensor type *	CMOS		

Lens system		Security	
Number of lenses *	1	Password protection	✓
Detect distance	70 m	IP address filtering	✓
Observe distance	29 m	Privacy protection	✓
Recognize distance	14 m	Digest authentication	✓
Focal length range	4 mm	Power	
Maximum aperture number	1	Power source type *	DC
Identify distance	7 m	Power consumption (max)	10.1 W
Minimum aperture number	1	DC output voltage	12
Fixed focal length	4 mm	Operational conditions	
Night vision		Operating temperature (T-T)	-30 - 60 °C
Night vision *	✓	Storage temperature (T-T)	-40 - 60 °C
Night vision distance	30 m	Operating relative humidity (H-H)	0 - 95%
LED type	White	Storage relative humidity (H-H)	0 - 95%
Number of illumination LEDs	4	Weight & dimensions	
		Width	102 mm
		Depth	236 mm
		Height	99 mm
		Packaging content	
		Number of cameras *	1



4895252500790

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-FEB-2025. Prints or copies of Information are only valid on the printed Publication date