

NETGEAR GS724TPv3 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs

Merk : NETGEAR

Artikelcode: GS724TPP-300EUS

Productnaam : GS724TPv3



NETGEAR GS724TPv3. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24, Aantal geïnstalleerde SFP modules: 2. Switchingcapaciteit: 52 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Power over Ethernet (PoE). Rack-montage

Beheerfuncties		Design	
Switch type *	Managed	Overtollige fans ondersteuning	✓
Switch-laag	L2	Aantal ventilatoren	2 ventilator(en)
Web-gebaseerd management	✓	Prestatie	
Cloud-beheerd	✓	Type processor	✓
Poorten & interfaces		Processorfabrikant	ARM
Aantal basis-switching RJ-45 Ethernet-poorten *	24	Processormodel	ARM Cortex-A55
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Frequentie van processor	800 MHz
Aantal geïnstalleerde SFP modules *	2	Intern geheugen	512 MB
Vezel-optische connector	SFP	Flash memory	64 MB
Netwerk		Geluidsniveau	26,1 dB
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x	Mean time between failures (MTBF)	1784610 uur
VLAN=ondersteuning	✓	Energie	
Aantal VLANs	256	Vermogenstoevoer inclusief *	✓
Data-uitwisseling		Stroomverbruik (typisch)	11,3 W
Switchingcapaciteit *	52 Gbit/s	Vermogensverbruik (max)	20,69 W
Packet buffergeheugen	1,5 MB	Power over Ethernet (PoE)	
Beveiliging		Power over Ethernet (PoE) *	✓
DHCP-functies	DHCP client, DHCP snooping	Aantal Power over Ethernet plus (PoE +)-poorten	24
Access Control List (ACL)	✓	Vermogen per poort Power over Ethernet (PoE)	190 W
Toegangsbeheerlijst (ACL) IPv4-vermeldingen	100	Totaal Power over Ethernet (PoE)-budget	231,07 W
IGMP snooping	✓	Eisen aan de omgeving	
Multicast-functies		Bedrijfstemperatuur (T-T)	0 - 50 °C
Multicast-ondersteuning	✓	Temperatuur bij opslag	-20 - 70 °C
Aantal gefilterde multicast-groepen	512	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
Design		Luchtvochtigheid bij opslag	0 - 95 procent
Rack-montage *	✓	Gewicht en omvang	
Kleur van het product	Grijs	Breedte	440 mm
LED-indicatoren	Activiteit, Link, Power over Ethernet (PoE), Stroom, Snelheid, Ja	Diepte	257 mm
		Hoogte	43,2 mm
		Gewicht	3,15 kg



0606449162769



606449162769

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.