



TP-Link VIGI C445 Torentje IP-beveiligingscamera Binnen & buiten

2688 x 1520 Pixels Plafond/muur

Merk : TP-Link **Productfamilie:** VIGI **Artikelcode:** VIGI-C455-4MM

Productnaam : C445

TP-Link VIGI C445. Soort: IP-beveiligingscamera, Ondersteuning voor plaatsing: Binnen & buiten, Connectiviteitstechnologie: Bedraad. Montagewijze: Plafond/muur, Kleur van het product: Wit, Vormfactor: Torentje. Minimale belichting: 0,005 Lux, Kijkhoek lens, horizontaal: 80.4°, Kijkhoek lens, verticaal: 41.8°. Type beeldsensor: CMOS, Omvang optische sensor: 25,4 / 2,7 mm (1 / 2.7"). Detectieafstand: 80 m, Observatieafstand: 33 m, Herkenningsafstand: 16 m



Performance		Video	
Type *	IP security camera	Maximum resolution *	2688 x 1520 pixels
Placement supported *	Indoor & outdoor	Total megapixels *	4 MP
Connectivity technology *	Wired	Video compression formats	H.264, H.264+, H.265, H.265+
Wide Dynamic Range (WDR)	✓	Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2550 x 1440, 2688 x 1520
Day/night mode	✓	Frame rate	60 fps
Infrared (IR) cut-off filter	✓	Noise reduction	✓
Dynamic range	120 dB	Noise reduction technology	3D noise reduction
Design		Bit rate control	Constant Bit Rate (CBR), Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Form factor *	Turret	Bit rate	6 Mbps
Mounting type *	Ceiling/wall	Region of Interest (ROI) encoding	✓
Product colour *	White	Smart IR	✓
Housing material	Metal, Plastic	Audio	
International Protection (IP) code	IP67	Built-in speaker(s)	✓
Camera		Sample rate	8 kHz
Camera pan control	✓	Signal-to-Noise Ratio (SNR)	52 dB
Camera tilt control	✓	Built-in microphone	✓
Minimum illumination	0.005 lx	Bit rate range	64 - 64 Kbit/s
Lens viewing angle, horizontal	80.4°	Network	
Lens viewing angle, vertical	41.8°	Ethernet LAN *	✓
Lens viewing angle, diagonal	98.7°	Ethernet interface type	Fast Ethernet
Tilt angle range	0 - 85°	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Pan range	0 - 360°		
Camera shutter speed	1/3 - 1/10000 s		
Number of Privacy masking areas	4		
Image sensor			
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")		
Progressive scan	✓		

Image sensor		Ports & interfaces	
Sensor type *	CMOS	Ethernet LAN (RJ-45) ports	1
Lens system		Security	
Number of lenses *	1	Password protection	✓
Detect distance	80 m	IP address filtering	✓
Observe distance	33 m	Privacy protection	✓
Recognize distance	16 m	Digest authentication	✓
Lens diameter	4 mm	Power	
Focal length range	4 mm	Power source type *	DC
Maximum aperture number	1.6	Power consumption (max)	10.1 W
Identify distance	8 m	Operational conditions	
Minimum aperture number	1.6	Operating temperature (T-T)	-30 - 60 °C
Fixed focal length	4 mm	Storage temperature (T-T)	-40 - 60 °C
Night vision		Operating relative humidity (H-H)	0 - 95%
Night vision *	✓	Storage relative humidity (H-H)	0 - 95%
Night vision distance	30 m	Weight & dimensions	
LED type	IR	Width	111 mm
Number of illumination LEDs	4	Depth	111 mm
Infra-red wavelength	850 nm	Height	83.7 mm
		Weight	480 g
		Packaging content	
		Number of cameras *	1



4895252506907

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-FEB-2025. Prints or copies of Information are only valid on the printed Publication date