

TP-Link VIGI C540-4G Torentje IP-beveiligingscamera Binnen & buiten 2560 x 1440 Pixels Plafond/muur

Merk : TP-Link

Productfamilie: VIGI

Artikelcode: VIGI
C540-4G(4MM)

Productnaam : C540-4G

TP-Link VIGI C540-4G. Soort: IP-beveiligingscamera, Ondersteuning voor plaatsing: Binnen & buiten, Connectiviteitstechnologie: Bedraad. Montagewijze: Plafond/muur, Kleur van het product: Zwart, Wit, Vormfactor: Torentje. Kijkhoek lens, horizontaal: 80°, Kijkhoek lens, verticaal: 43°, Kijkhoek lens, diagonaal: 94°. Type beeldsensor: CMOS, Omvang optische sensor: 25,4 / 3,06 mm (1 / 3.06"). Detectieafstand: 80 m, Observatieafstand: 33 m, Herkenningsafstand: 16 m



Performance		Video	
Type *	IP security camera	Digital Wide Dynamic Range (DWDR)	✓
Placement supported *	Indoor & outdoor	3D positioning	✓
Connectivity technology *	Wired	Audio	
Auto patrol mode	✓	Built-in speaker(s)	✓
Wide Dynamic Range (WDR)	✓	Sample rate	8 kHz
Day/night mode	✓	Signal-to-Noise Ratio (SNR)	52 dB
Infrared (IR) cut-off filter	✓	Built-in microphone	✓
Luminous flux	0.005 lm	Bit rate range	64 - 64 Kbit/s
Certification	RCM, BSMI, VCCI, NTRA, KC	Network	
Design		Ethernet LAN *	✓
Form factor *	Turret	Ethernet interface type	Fast Ethernet
Mounting type *	Ceiling/wall	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Product colour *	Black, White	SIM card slot	✓
Housing material	Plastic	SIM card type	NanoSIM
International Protection (IP) code	IP66	4G standard	LTE-TDD & LTE-FDD
Camera		3G standards	WCDMA
Camera pan control	✓	Live view	✓
Camera tilt control	✓	Number of simultaneous live view channels	3 channels
Lens viewing angle, horizontal	80°	Storage	
Lens viewing angle, vertical	43°	Built-in HDD *	✗
Lens viewing angle, diagonal	94°	Card reader integrated	✓
Tilt angle range	0 - 120°	Compatible memory cards	MicroSD (TransFlash)
Tilt speed	44 °/sec	Maximum memory card size	256 GB
Pan range	0 - 348°		
Pan speed	44 °/sec		
Camera shutter speed	1/3 - 1/10000 s		
Number of Privacy masking areas	4		

Image sensor		Ports & interfaces	
Optical sensor size	25.4 / 3.06 mm (1 / 3.06")	Ethernet LAN (RJ-45) ports	1
Sensor type *	CMOS	Security	
Lens system		Password protection	✓
Zoom capability	✓	IP address filtering	✓
Number of lenses *	1	HTTPS encryption	✓
Detect distance	80 m	Intelligent Video Surveillance (IVS) system features	Human detection
Observe distance	33 m	Mirror	✓
Recognize distance	16 m	Digest authentication	✓
Lens diameter	4 mm	Management features	
Maximum aperture number	1.6	Reset button	✓
Identify distance	8 m	Behavior analysis	Intrusion detection, Line crossing detection
Minimum aperture number	1.6	Power	
Night vision		Power source type *	DC
Night vision *	✓	DC output voltage	12
Night vision distance	30 m	Operational conditions	
LED type	IR/White	Operating temperature (T-T)	-30 - 60 °C
Number of illumination LEDs	4	Storage temperature (T-T)	-40 - 60 °C
Video		Operating relative humidity (H-H)	0 - 95%
Maximum resolution *	2560 x 1440 pixels	Storage relative humidity (H-H)	0 - 95%
Total megapixels *	4 MP	Weight & dimensions	
Video compression formats	H.264, H.264+, H.265, H.265+ 320 x 240, 352 x 288, 640 x 480 (VGA), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440	Width	120 mm
Supported graphics resolutions		Depth	182 mm
Frame rate	30 fps	Height	201 mm
Video streaming	✓	Weight	690 g
Noise reduction	✓	Features	
Noise reduction technology	3D noise reduction	Basic event	Motion Detection, Camera Tampering Detection, Exception
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Packaging data	
Privacy masking	✓	Package width	163 mm
Bit rate control	Constant Bit Rate (CBR), Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Package depth	213 mm
Bit rate	256 Kbps - 4 Mbps	Package height	243 mm
		Package weight	1.16 kg
		Sustainability	
		Compliance certificates	CE, RoHS
		Packaging content	
		Number of cameras *	1
		Mounting kit	✓



4895252504910



4895252504927

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-FEB-2025. Prints or copies of Information are only valid on the printed Publication date