tp-link

TP-Link Omada EAP615-WALL 1774 Mbit/s Wit Power over Ethernet (PoE)

Merk : TP-Link

Productfamilie: Omada

Artikelcode: EAP615-WALL(5-PACK)

Productnaam : EAP615-WALL

TP-Link Omada EAP615-WALL. 2,4 GHz, 5 GHz, Maximale overdrachtssnelheid van gegevens: 1774 Mbit/s. Ondersteunde beveiligingsalgoritmen: HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal,.... Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Kleur van het product: Wit

Features

2.4 GHz *	✔
5 GHz *	✔
6 GHz *	✗
Maximum data transfer rate *	1774 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	1201 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Cabling technology	10/100/1000Base-T(X)
Automatic channel selection	✔
Automatic channel scanning	✔
MIMO	✔
MIMO type	Multi User MIMO
VLAN support	✔
Rate limiting	✔
Wireless isolation	✔
Band steering	✔
Airtime Fairness (ATF)	✔
Quality of Service (QoS) support	✔
BeamForming	✔
Transmitting power (CE)	23 dBm
Transmitting power (FCC)	21 dBm

Ports & interfaces

Ethernet LAN (RJ-45) ports *	4

Power

Power over Ethernet (PoE) *	✔
Power consumption (typical)	10 W

Design

Placement *	Wall
Product colour *	White
Cable lock slot	✔
On/off switch	✔
Reset button	✔
LED indicators	Power

Antenna

Antenna type *	Internal
Antennas quantity	4
Antenna gain level (max)	4 dBi

Performance

Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Windows 11, Linux

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS

Weight & dimensions

Width	143 mm
Depth	86 mm
Height	20 mm

Security

Security algorithms *	HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal
MAC address filtering	✔
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	16
Remote Authentication Dial-In User Service (RADIUS)	✔
Access Control List (ACL)	✔

Protocols

STelnet using SSH v2	✔

Management features

Web-based management	✔
Syslog	✔
Firmware upgradeable	✔

Packaging data

Package width	385 mm
Package depth	495 mm
Package height	210 mm
Package weight	330 g

Packaging content

Quantity per pack	5 pc(s)
Mounting kit	✔
Quick start guide	✔

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%

8885020622898