


DeepCool PN650M power supply unit 650 W 20+4 pin ATX ATX
Zwart

Merk : DeepCool

Artikelcode: R-PN650M-FC0B-EU

Productnaam : PN650M



DeepCool PN650M. Totaal vermogen: 650 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 550,750,450,650 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Meegeleverde kabels: AC

Energie		Poorten & interfaces	
Totaal vermogen *	650 W	CPU power connector (4+4 pin)	✓
AC-ingangsspanning *	100 - 240 V	Lengte CPU-stroomkabel	70 cm
AC-ingangsfrequentie	50/60 Hz	ATX power connector (20+4 pin)	✓
Stroom	10 - 5 A	Bekabelingstype	Volledig modulair
Power Factor Correctie (PFC) type	Actief	Prestatie	
Gecombineerd vermogen (+3.3V)	100 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (+12V)	648 W	Bedoeld voor *	PC
Gecombineerd vermogen (+5V)	100 W	Vormfactor van de voeding (PSU) *	ATX
Gecombineerd vermogen (-12V)	3,6 W	ATX version	3.1
Gecombineerd vermogen(+5Vsb)	15 W	Bearing technologie	FDB
Max huidige output (+3.3V)	20 A	Mean time between failures (MTBF)	100000 uur
Max huidige output(+12V)	54 A	Design	
Max huidige output (+5V)	20 A	Kleur van het product	Zwart
Max huidige output (-12V)	0,3 A	Type koeling	Actief
Max huidige output (+5Vsb)	3 A	Ventilator diameter	12 cm
Houd-tijd	16 ms	Aantal ventilatoren	1 ventilator(en)
Efficiëntie	90 procent	Ventilator locatie	Boven
Stroomspanning bescherming	No load operation, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Surge & inrush protection (SIP), Overspanningsbeveiliging, Onder spanning	Aan/uitschakelaar	✓
		Eisen aan de omgeving	
Poorten & interfaces		Bedrijfstemperatuur (T-T)	0 - 40 °C
Motherboard power connector *	20+4 pin ATX	Inhoud van de verpakking	
Lengte stroomkabel moederbord	55 cm	Meegeleverde kabels	AC
Aantal SATA power connectors	8	Inclusief kabelbinder(s)	✓
Lengte SATA-stroomkabel	550,750,450,650 mm	Gewicht en omvang	
Peripheral (Molex) power connectors (4-pin) *	2	Breedte	150 mm
Lengte stroomkabel randapparaat (Molex)	450 mm	Diepte	140 mm
PCI Express power connectors (6+2 pin)	3	Hoogte	86 mm
		Verpakking	
		Type verpakking	Doos

Poorten & interfaces		Technische details	
PCI Express-voedingsconnectoren (16-pins)	1	Duurzaamheidscertificaten	Triman
		Garantieperiode	10 jaar
		Certificaten van naleving	CCC, CE, EAC, Federal Communications Commission (FCC), RCM, RoHS, WEEE



6933412719236

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-SEP-2024. Prints or copies of Information are only valid on the printed Publication date