NETGEAR GS305Pv3 Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk: NETGEAR Artikelcode: GS305P-300EUS

Productnaam: GS305Pv3



NETGEAR GS305Pv3. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. Full duplex. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC voltage input: 54 V. Netstekker: DC-in ingang. Power over Ethernet (PoE). Ophangsysteem voor aan de muur



| Management features | | Design | |
|---|------------------------------------|--|----------------------------|
| Switch type * | Unmanaged | Stackable * | × |
| Quality of Service (QoS) support | ✓ | Product colour | Black |
| Ports & interfaces | | LED indicators | ✓ |
| Basic switching RJ-45 Ethernet ports | _ | Wall mountable | ✓ |
| quantity * | 5 | Performance | |
| Basic switching RJ-45 Ethernet ports type * | Gigabit Ethernet (10/100/1000) | Mean time between failures (MTBF) | 4113947 h |
| Power connector | DC-in jack | Power | |
| Network | | Power source * | DC |
| | IEEE 802.1p, IEEE 802.3, IEEE | DC input voltage | 54 V |
| Networking standards * | 802.3ab, IEEE 802.3i, IEEE 802.3u, | Input current | 1.25 A |
| 100 | IEEE 802.3x | Power consumption (max) | 66.78 W |
| 10G support * | X | Power over Ethernet (PoE) | |
| Full duplex | ✓ | Power over Ethernet (PoE) * | 1 |
| Half duplex | 1 | Power over Ethernet (PoE) power | 30 W |
| Flow control support | 1 | per port | 30 W |
| Auto MDI/MDI-X | 1 | Total Power over Ethernet (PoE) budget | 63 W |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | | |
| Auto-sensing | 1 | Operational conditions | |
| Data transmission | | Operating temperature (T-T) | 0 - 40 °C |
| Switching capacity * | 10 Gbit/s | Operating relative humidity (H-H) | 0 - 90% |
| MAC address table * | 2000 entries | Operating altitude Heat dissipation | 0 - 3000 m 228.38 BTU/h |
| Jumbo frames support | ✓ | | 220.30 010/11 |
| Jumbo frames | 9216 | Weight & dimensions | |
| Packet forwarding rate (1 Gbps) | 1448000 pps | Width | 158 mm |
| Packet buffer memory | 0.128 MB | Depth | 101 mm |
| Design | | Height | 27 mm |
| Rack mounting * | × | Weight | 400 g |





606449164909

0606449164909

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.