NETGEAR GS305PP Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk: NETGEAR Artikelcode: GS305PP-300EUS

Productnaam: GS305PP







Management features		Power	
Switch type *	Unmanaged	Input current	1.66 A
Quality of Service (QoS) support	✓	Power consumption (typical)	2.89 W
Ports & interfaces		Power consumption (max)	88.89 W
Basic switching RJ-45 Ethernet ports	4	Power over Ethernet (PoE)	
quantity * Basic switching RJ-45 Ethernet ports		Power over Ethernet (PoE) *	1
type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet plus (PoE+) ports quantity	4
Gigabit Ethernet (copper) ports quantity	5	Power over Ethernet (PoE) power per port	30 W
Power connector	DC-in jack	Total Power over Ethernet (PoE)	83 W
Network		budget	0.5 VV
Networking standards * 8	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
10G support *	X	Storage temperature (T-T)	-20 - 70 °C
	10BASE-T, 100BASE-TX, 1000BASE-	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 95%
Copper ethernet cabling technology	Т	Heat dissipation	304 BTU/h
Full duplex	✓	Weight & dimensions	30.13.13/
Auto MDI/MDI-X	✓	Width	158 mm
Auto-sensing	✓	Depth	101 mm
Auto-negotiation	✓	Height	29 mm
Cable length detection	✓	Weight	410 g
Data transmission		Packaging content	
Switching capacity *	10 Gbit/s	Manual	1
Forwarding rate MAC address table *	1.448 Mpps 2000 entries	Packaging data	
Latency (1 Gbps)	2.4 μs	Package width	269 mm
Jumbo frames support	✓	Package depth	73 mm
Jumbo frames	9216	Package height	215 mm
Packet buffer memory	128 MB	Package weight	1.3 kg
Design		Certificates	
Rack mounting *	×	Certification	CE Mark, FCC Part 15 Class B, IC Class B, RCM, CCC, VCCI, CB, CE VD
Product colour	Black	33 38. loll	CCC
Housing material	Metal	Logistics data	
Reset button	✓	Master (outer) case width	237 mm
LED indicators	Activity, Link, PoE, Power	Master (outer) case length	469 mm
Wall mountable		_	

Performance		Logistics data	
Mean time between failures (MTBF)	6710127 h	Master (outer) case gross weight	8.52 kg
Power		Products per master (outer) case	6 pc(s)
Power source *	DC		
DC input voltage	54 V		





606449164916

0606449164916

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.