



TP-Link LiteWave LS105GP netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : TP-Link

Productfamilie: LiteWave

Artikelcode: LS105GP

Productnaam : LS105GP



TP-Link LiteWave LS105GP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC voltage input: 53.5 V. Power over Ethernet (PoE)



Beheerfuncties		Energie	
Switch type *	Unmanaged	Stroombron *	DC/PoE
Quality of Service (QoS)	✓	Vermogenstoevoer inclusief *	✓
Poorten & interfaces		AC-ingangsspanning	220 V
Aantal basis-switching RJ-45 Ethernet-poorten *	5	AC-ingangsfrequentie	50 Hz
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	DC voltage input	53.5 V
Netwerk		Vermogensverbruik (max)	74,46 W
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Ondersteunde kabel types	Cat3, Cat5e, Cat4, Cat5	Hoeveelheid Power over Ethernet (PoE) ports	4
Datastroombeheer	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Auto MDI/MDI-X	✓	Totaal Power over Ethernet (PoE)-budget	65 W
Auto-negotiation	✓	Eisen aan de omgeving	
MAC-adres zelflerende functie	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
MAC-adres zelfverouderende functie	✓	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	10 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	7,44 Mpps	Warmtedissipatie	253,16 BTU/h
MAC-adrestabel *	2000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	99,8 mm
Jumbo frames	16000	Diepte	98 mm
Beveiliging		Hoogte	25 mm
IGMP snooping	✓	Inhoud van de verpakking	
		Gebruiksaanwijzing	✓

Design		Verpakking	
Kleur van het product	Zwart	Type verpakking	Doos
LED-indicatoren	✓	Certificaten	
		Certificering	CE, FCC, RoHS



4895252504552



4895252504545

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.