



TP-Link LiteWave LS108GP netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : TP-Link

Productfamilie: LiteWave

Artikelcode: LS108GP

Productnaam : LS108GP



TP-Link LiteWave LS108GP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 8. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 16 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE.... DC voltage input: 53.5 V. Netstekker: DC-in ingang. Power over Ethernet (PoE)



Beheerfuncties		Energie	
Switch type *	Unmanaged	DC voltage input	53.5 V
Quality of Service (QoS)	✓	Stroom	1.31 A
Poorten & interfaces		Vermogensverbruik (max)	71,61 W
Aantal basis-switching RJ-45 Ethernet-poorten *	8	Power over Ethernet (PoE)	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) *	✓
Netstekker	DC-in ingang	Aantal Power over Ethernet plus (PoE +)-poorten	8
Netwerk		Vermogen per poort Power over Ethernet (PoE)	30 W
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Totaal Power over Ethernet (PoE)-budget	62 W
10G support *	✗	Eisen aan de omgeving	
Ondersteundende kabel types	Cat3, Cat4, Cat5, Cat5e	Bedrijfstemperatuur (T-T)	0 - 40 °C
Datastroombeheer	✓	Temperatuur bij opslag	-40 - 70 °C
Auto MDI/MDI-X	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Auto-negotiation	✓	Luchtvochtigheid bij opslag	5 - 90 procent
Data-uitwisseling		Warmte-dissipatie	243,47 BTU/h
Switchingcapaciteit *	16 Gbit/s	Gewicht en omvang	
Verzending snelheid	11,9 Mpps	Breedte	158 mm
MAC-adrestabel *	4000 entries	Diepte	99 mm
Jumbo frames	16000	Hoogte	25 mm
Design		Inhoud van de verpakking	
Kleur van het product	Zwart	Gebruiksaanwijzing	✓
LED-indicatoren	✓	Verpakking	
		Type verpakking	Doos

Energie		Certificaten	
Stroombron *	DC/PoE	Certificering	CE, FCC, RoHS
Vermogenstoevoer inclusief *	✓		
AC-ingangsspanning	220 V		
AC-ingangsfrequentie	50 Hz		



4895252505993



4895252505986

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.