


NETGEAR GS752TXP Managed L2/L3/L4 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) Zwart

Merk : NETGEAR

Artikelcode: GS752TXP-300EUS

Productnaam : GS752TXP



NETGEAR GS752TXP. Switch type: Managed, Switch-laag: L2/L3/L4. Type basis-switching RJ-45 Ethernet-poorten: 10G Ethernet (100/1000/10000), Aantal basis-switching RJ-45 Ethernet-poorten: 48. Full duplex. MAC-adrestabel: 16000 entries. Netwerkstandaard: IEEE 802.1ab, IEEE 802.1as, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Power over Ethernet (PoE). Rack-montage

Beheerfuncties		Design	
Switch type *	Managed	Rack-montage *	✓
Switch-laag	L2/L3/L4	Stapelbaar *	✓
Poorten & interfaces		Kleur van het product	Zwart
Aantal basis-switching RJ-45 Ethernet-poorten *	48	Prestatie	
Type basis-switching RJ-45 Ethernet-poorten *	10G Ethernet (100/1000/10000)	Type processor	✓
Aantal moduleslots SPF+	4	Flash memory	64 MB
Netwerk		Geluidsniveau	36,6 dB
Netwerkstandaard *	IEEE 802.1ab, IEEE 802.1as, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Mean time between failures (MTBF)	1296949 uur
		Energie	
10G support *	✓	Stroombron *	AC
Port mirroring	✓	Vermogenstoevoer inclusief *	✓
Full duplex	✓	Vermogensverbruik (max)	51 W
Datastroombeheer	✓	Power over Ethernet (PoE)	
Verbindingsaggregatie	✓	Power over Ethernet (PoE) *	✓
Broadcast stormbeheer	✓	Aantal Power over Ethernet plus (PoE +)-poorten	48
Rate limiting	✓	Totaal Power over Ethernet (PoE)-budget	380 W
Spanning tree protocol	✓	Eisen aan de omgeving	
VLAN=ondersteuning	✓	Bedrijfstemperatuur (T-T)	0 - 50 °C
Virtuele LAN-functies	Voice VLAN	Temperatuur bij opslag	-20 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
MAC-adrestabel *	16000 entries	Luchtvochtigheid bij opslag	0 - 95 procent
Latentie (10 Gbps)	4,107 µs	Hoogte, in bedrijf	0 - 3000 m
Statische route	✓	Hoogte bij opslag	0 - 3000 m
Aantal statische routes	32	Warmtedissipatie	2944,6 BTU/h
Packet buffergeheugen	16 MB	Gewicht en omvang	
Beveiliging		Breedte	440 mm
DHCP-functies	DHCP client	Diepte	345 mm
Access Control List (ACL)	✓	Hoogte	43 mm
IGMP snooping	✓	Gewicht	5,54 kg
MAC adres filtering	✓		
SSH/SSL support	✓		



0606449171181



606449171181

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.