

Overview

HPE OfficeConnect 1820 Switch Series



Models

HPE OfficeConnect 1820 8G Switch	J9979A
HPE OfficeConnect 1820 8G PoE+ (65W) Switch	J9982A
HPE OfficeConnect 1820 24G Switch	J9980A
HPE OfficeConnect 1820 24G PoE+ (185W) Switch	J9983A
HPE OfficeConnect 1820 48G Switch	J9981A
HPE OfficeConnect 1820 48G PoE+ (370W) Switch	J9984A

Key features

- Customized operation using intuitive Web interface
- Flexible deployment options including wall, under table and desktop mounting
- 24- and 48 port models include SFP ports
- 8-, 24- and 48 port non-PoE+ models are fanless for quiet operation
- Limited lifetime Warranty

Product overview

Overview

HPE OfficeConnect 1820 Switch Series devices are basic, smart-managed, fixed-configuration Gigabit Ethernet Layer 2 switches designed for small businesses looking for key features in an easy-to-administer solution. The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business networking products.

The series consists of six switches including 8-, 24- and 48-port Gigabit Ethernet switches and 8-, 24-, and 48-port Gigabit PoE+ models each providing non-blocking Gigabit per port performance. Some models include SFP ports for fiber connectivity and the 8-, 24-, and 48-port non PoE+ models are fanless, making them ideal for office deployments. All HPE OfficeConnect 1820 Switches support flexible installation options, including mounting on wall, under table, or on desktop. The 8-port Gigabit Ethernet model can be powered by an upstream Power over Ethernet (PoE) switch for environments where no line power is available.

These Gigabit switches are plug-and-play out of the box, yet network operation can be fine-tuned through features available from a simple Web browser-based GUI, if necessary. Customizable features include VLANs, Rapid Spanning Tree, IGMP Snooping, link aggregation trunking, and DSCP QoS policies. All models include the latest energy-saving capabilities, including Energy Efficient Ethernet (EEE) and idle-port power down. HPE OfficeConnect 1820 Switch Series includes a Limited Lifetime Warranty. This warranty provides advance hardware replacement with next business day shipment in most countries, limited 24x7 telephone support available from HPE for the first 90 days, and limited electronic and business hours telephone support is available from HPE for the entire warranty period.

Features and Benefits

Management

- **Simple Web management**
Allows for easy management of the switch—even by nontechnical users—through an intuitive Web GUI; supports HTTP and HTTP Secure (HTTPS).
- **SNMPv1, v2c**
Enables devices to be discovered and monitored from an SNMP management station.
- **Port mirroring**
Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring.
- **Dual flash images**
Provides independent primary and secondary operating system files for backup while upgrading.
- **Network Time Protocol (NTP)**
Synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network.
- **Manual network time configuration**
Manually set the date and time on the switch in the absence of an NTP server.
- **Default DHCP client mode**
Allows the switch to be directly connected to a network, enabling plug-and-play operation; in absence of a DHCP server on the network, the switch falls back to a default, fixed IP address.

Quality of Service (QoS)

- **Traffic prioritization**
Provides time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification; packets are mapped to eight hardware queues for more effective throughput.
- **Broadcast control**
Allows limiting of broadcast traffic rate to reduce unwanted network broadcast traffic.
- **IEEE 802.1p/Q**

Overview

Delivers data to devices based on the priority and type of traffic; supports IEEE 802.1Q.

Connectivity

- **Auto-MDI/MDIX**
Automatically adjusts for straight-through or crossover cables on all ports.
- **IEEE 802.3X flow control**
Provides a flow throttling mechanism propagated through the network to prevent packet loss at a congested node.
- **Loop protection**
If the switch detects a loop, it disables the source port from forwarding data packets originating from the switch to avoid broadcast storms.
- **SFP ports for fiber connectivity**
Provides fiber connections for uplinks and other connections across longer distances than copper cabling can support; SFP ports are in addition to available copper Ethernet ports, providing a higher total number of available ports. SFP ports available on 24- and 48 port models.
- **IEEE 802.3af PoE-powered device option**
Obtains power provided by a standard PoE device connected to Port 1; deploy the switch wherever an Ethernet cable can reach as a power outlet is not needed (8-port GbE non-PoE+ model only).
- **IEEE 802.3at Power over Ethernet (PoE+)**
Provides up to 30W per port, which allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; lowers the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments.
- **PoE+ port availability**
Ports 1-4 provide PoE+ on the HPE 1820-8G-PoE+ (65W) switch. Ports 1 – 12 provide PoE+ on the HPE 1820-24G-PoE+ (180W) switch. Ports 1-24 provide PoE+ on the HPE 1820-48G-PoE+ (370W) switch.
- **Auto PoE power configuration**
The switch automatically assigns the required power to a port for a PD device based on LLDP (Link Layer Discovery Protocol). Optionally, the switch permits manual, per port, PoE power configuration.
- **PoE shut down mode**
A PoE scheduler provides the ability to define the hours of PoE power being supplied on a group of switch ports based on a 24 hour day. The scheduler enables the flexibility to select individual days of a week as well as reoccurrence on a weekly basis with a start and end date.
- **Energy Efficient Ethernet**
Compliant with IEEE 802.3az standard requirements to save energy during periods of low data activity.
- **Auto port shut-down**
The switch saves power by automatically shutting down power to inactive ports. Power is restored on a port upon link detection.
- **Energy savings status**
The switch provides an estimated cumulative energy savings due to green Ethernet features enabled.

Security

- **Secure Sockets Layer (SSL)**
Encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch.
- **Automatic denial-of-service protection**
Monitors nine types of malicious attacks and protects the network by blocking these attacks.
- **Management password**
Provides security so that only authorized access to the Web browser interface is allowed.

Overview

Performance

- **Half-/full-duplex auto-negotiating capability on every port**
Doubles the throughput of every port.
- **IGMP snooping**
Improves network performance through multicast filtering, instead of flooding traffic to all ports.

Layer 2 switching

- **VLAN support and tagging**
Supports up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups.
- **Jumbo packet support**
Improves the performance of large data transfers; supports frame size of up to 9220 bytes.

Resiliency and high availability

- **IEEE 802.1D Spanning Tree Protocol (STP) and IEEE 802.1W Rapid Spanning Tree Protocol (RSTP)**
Provides redundant links while preventing network loops.
- **Link aggregation**
Brings together groups of ports automatically using Link Aggregation Control Protocol (LACP) or, manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks; the 8 port models support 4 trunks, the 24-port models support 8 trunks and the 48-port models support 16 trunks. The 8- and 24-port switches can support up to 4 ports per trunk, the 48-port switches can support up to 8 ports per trunk

Ease of use

- **Locator LED**
Allows users to set the locator LED on a specific switch to either turn on, blink, or turn off; simplifies troubleshooting by making it easy to locate a particular switch within a rack of similar switches.
- **Comprehensive LED display with per-port indicators**
Provides an at-a-glance view of status, activity, speed, and full-duplex operation.

Flexibility

- **Flexible installation**
Allows mounting on wall, desktop, or under-table with supplied hardware.
- **Rack mountable**
All models include rack-mounting hardware for mounting in a standard 19 inch telco rack.
- **Kensington lock slot**
Allows switches to be physically secured in open-space deployments (8-,and 24 port models).

Warranty and support

- **Limited Lifetime Warranty**
This series comes with a Limited Lifetime Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and electronic and business hours phone support for the entire warranty period. See <http://www.hpe.com/networking/warrantysummary> for full warranty and

Overview

support information included with your product purchase.

Configuration

Build To Order:

BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HPE OfficeConnect 1820 8G Switch	J9979A
<ul style="list-style-type: none"> 8 RJ-45 autosensing 10/100/1000 ports 1U - Height (Desktop Model) 	See Configuration NOTE:2
HPE OfficeConnect 1820 24G Switch	J9980A
<ul style="list-style-type: none"> 24 RJ-45 autosensing 10/100/1000 ports 2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers) 1U - Height 	See Configuration NOTE:1, 3
PDU Cable NA/MEX/TW/JP	J9980A#B2B
<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable NA/MEX/TW/JP	J9980A#B2C
<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
High Volt Switch/Router to Wall Power Cord	J9980A#B2E
<ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) 	
HPE OfficeConnect 1820 48G Switch	J9981A
<ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers) 1U - Height 	See Configuration NOTE:1, 3
PDU Cable NA/MEX/TW/JP	J9981A#B2B
<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable NA/MEX/TW/JP	J9981A#B2C
<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
High Volt Switch/Router to Wall Power Cord	J9981A#B2E
<ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) 	
HPE OfficeConnect 1820 8G PoE+ (65W) Switch	J9982A
<ul style="list-style-type: none"> 4 RJ-45 autosensing 10/100/1000 PoE+ ports 4 RJ-45 autosensing 10/100/1000 ports 1U - Height (Desktop Model) 	See Configuration NOTE:2
HPE OfficeConnect 1820 24G PoE+ (185W) Switch	J9983A

Configuration

<ul style="list-style-type: none"> • 12 RJ-45 autosensing 10/100/1000 PoE+ ports • 12 RJ-45 autosensing 10/100/1000 ports • 2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers) • 1U - Height 	See Configuration NOTE:1, 3
PDU Cable NA/MEX/TW/JP <ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	J9983A#B2B
PDU Cable NA/MEX/TW/JP <ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	J9983A#B2C
High Volt Switch/Router to Wall Power Cord <ul style="list-style-type: none"> • NEMA L6-20P Cord (NA/MEX/JP/TW) 	J9983A#B2E
HPE OfficeConnect 1820 48G PoE+ (370W) Switch <ul style="list-style-type: none"> • 24 RJ-45 autosensing 10/100/1000 PoE+ ports • 24 RJ-45 autosensing 10/100/1000 ports • 4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers) • 1U - Height 	J9984A See Configuration NOTE:1, 3
PDU Cable NA/MEX/TW/JP <ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	J9984A#B2B
PDU Cable NA/MEX/TW/JP <ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	J9984A#B2C
High Volt Switch/Router to Wall Power Cord <ul style="list-style-type: none"> • NEMA L6-20P Cord (NA/MEX/JP/TW) 	J9984A#B2E
Configuration Rules:	
Note 1	"The following Transceivers install into this switch:
	HPE X121 1G SFP LC SX Transceiver J4858C
	HPE X121 1G SFP LC LX Transceiver J4859C
	HPE X111 100M SFP LC FX Transceiver J9054C
	HPE X121 1G SFP RJ45 T Transceiver J8177C
Note 2	Localization required. (See Localization Menu for list.)
Note 3	Localization (Wall Power Cord) required on orders without #B2B or #B2C (PDU Power Cord). (See Localization Menu)

Rack Level Integration CTO Models

Configuration

HPE OfficeConnect 1820 24G Switch	J9980A
<ul style="list-style-type: none"> • 24 RJ-45 autosensing 10/100/1000 ports • 2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers) • 1U - Height 	See Configuration NOTE: 1, 2, 3
PDU Cable NA/MEX/TW/JP	J9980A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable NA/MEX/TW/JP	J9980A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
HPE OfficeConnect 1820 48G Switch	J9981A
<ul style="list-style-type: none"> • 48 RJ-45 autosensing 10/100/1000 ports • 4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers) • 1U - Height 	See Configuration NOTE: 1, 2, 3
PDU Cable NA/MEX/TW/JP	J9981A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable NA/MEX/TW/JP	J9981A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
HPE OfficeConnect 1820 24G PoE+ (185W) Switch	J9983A
<ul style="list-style-type: none"> • 12 RJ-45 autosensing 10/100/1000 PoE+ ports • 12 RJ-45 autosensing 10/100/1000 ports • 2 SFP 100/1000 Mbps ports (min=0 \ max=2 SFP Transceivers) • 1U - Height 	See Configuration NOTE: 1, 2, 3
PDU Cable NA/MEX/TW/JP	J9983A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable NA/MEX/TW/JP	J9983A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
HPE OfficeConnect 1820 48G PoE+ (370W) Switch	J9984A
<ul style="list-style-type: none"> • 24 RJ-45 autosensing 10/100/1000 PoE+ ports • 24 RJ-45 autosensing 10/100/1000 ports • 4 SFP 100/1000 Mbps ports (min=0 \ max=4 SFP Transceivers) • 1U - Height 	See Configuration NOTE: 1, 2, 3
PDU Cable NA/MEX/TW/JP	J9984A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable NA/MEX/TW/JP	J9984A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	

Configuration

Configuration Rules:

- Note 1 The following Transceivers install into this switch
- | | |
|-------------------------------------|--------|
| HPE X121 1G SFP LC SX Transceiver | J4858C |
| HPE X121 1G SFP LC LX Transceiver | J4859C |
| HPE X111 100M SFP LC FX Transceiver | J9054C |
| HPE X121 1G SFP RJ45 T Transceiver | J8177C |
- Note 2 Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) . (See Localization Menu)
REMARK: When Switches/Routers are Factory Racked, Then #B2B, or #B2C should be the Defaulted Power Cable option on the Switches/Routers.
- Note 3 If this switch is factory installed in any HPE Racks, Then the J9583A#OD1 is required.

Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

Transceivers

SFP Transceivers

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X111 100M SFP LC FX Transceiver	J9054C

Internal Power Supplies

Power supplies included

Remarks:

Drop down under power supply should offer the following options and results:

Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)

Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)

High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)

Cables

Multi-Mode Cables

Configuration

HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HP LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Switch Enclosure Options

Rack Mount Kit

HPE X410 1U Universal 4-post Rackmount Kit

- Supported on J9980A, J9981A, J9983A, J9984A

J9583A

See Configuration

NOTE:1

Configuration Rules:

Note 1 If this Mounting Kit is order with #OD1 then it integrates to the HPE Network Rack. (not the switch)

Technical Specifications

HPE OfficeConnect 1820 I/O ports and slots 8G Switch (J9979A)

8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

Supports a maximum of 8 autosensing 10/100/1000 ports

Physical characteristics	Dimensions	10(w) x 6.28(d) x 1.73(h) in (25.4 x 15.95 x 4.39 cm) (1U height)
	Weight	1.81 lb (0.82 kg)
Memory and processor	ARM Cortex-A9 @ 400 MHz, 128 MB SDRAM; Packet buffer size: 1.5 MB, 16 MB flash	
Performance	100 Mb Latency	< 7 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2.4 μ s (LIFO 64-byte packets)
	Throughput	up to 11.9 Mpps (64-byte packets)
	Switching capacity	16 Gbps
	MAC address table size	8000 entries
Reliability	MTBF (years)	144.93
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C)
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)
	Altitude	up to 9,842 ft (3 km)
	Acoustic	Power: 0 dB no fan
Electrical characteristics	Frequency	50/60 Hz
	AC Voltage	100 - 240 VAC
	Current	.2 A
	Maximum power rating	12.2 W
	Idle power	10.2 W
	PoE power	
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; EN 60825; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1	

Technical Specifications

Emissions	FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A F
Immunity	<p>Generic EN 55024, CISPR 24</p> <p>EN EN 55024, CISPR 24</p> <p>ESD IEC 61000-4-2</p> <p>Radiated IEC 61000-4-3</p> <p>EFT/Burst IEC 61000-4-4</p> <p>Surge IEC 61000-4-5</p> <p>Conducted IEC 61000-4-6</p> <p>Power frequency magnetic field IEC 61000-4-8</p> <p>Voltage dips and interruptions IEC 61000-4-11</p> <p>Harmonics EN 61000-3-2, IEC 61000-3-2</p> <p>Flicker EN 61000-3-3, IEC 61000-3-3</p>
Management	Web browser
Notes	Use only supported genuine HPE mini-GBICs with your switch
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE OfficeConnect 1820 I/O ports and slots 8G PoE+ (65W) Switch (J9982A)

	4 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
	4 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
Physical characteristics	<p>Dimensions 10(w) x 6.28(d) x 1.73(h) in (25.4 x 15.95 x 4.39 cm) (1U height)</p> <p>Weight 2.01 lb (0.91 kg)</p>
Memory and processor	ARM Cortex-A9 @ 400 MHz, 128 MB SRAM; Packet buffer size: 1.5 MB, 16 MB flash
Performance	<p>100 Mb Latency < 7 μs (LIFO 64-byte packets)</p> <p>1000 Mb Latency < 2.3 μs (LIFO 64-byte packets)</p> <p>Throughput up to 11.9 Mpps (64-byte packets)</p> <p>Switching capacity 16 Gbps</p> <p>MAC address table size 8000 entries</p>
Reliability	MTBF (years) 112.36
Environment	<p>Operating temperature 32°F to 104°F (0°C to 40°C)</p> <p>Operating relative humidity 15% to 95% @ 104°F (40°C)</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p>

Technical Specifications

	Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)
	Altitude	up to 9,842 ft (3 km)
	Acoustic	Power: 0 dB no fan
Electrical characteristics	Frequency	50/60 Hz
	AC Voltage	100 - 240 VAC
	Current	.9 A
	Maximum power rating	83.9 W
	Idle power	12.6 W
	PoE power	65 W PoE+
	Notes	<p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of an External Power Supply (EPS).</p>
	Safety	UL 60950-1; EN 60825; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1
Emissions	FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A	
Immunity	Generic	EN 55024, CISPR 24
	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	
Management	Web browser	
Notes	Use only supported genuine HPE mini-GBICs with your switch	
Services	<p>Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-</p>	

Technical Specifications

level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE OfficeConnect 1820 I/O ports and slots	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
24G Switch (J9980A)	2 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)	
	Supports a maximum of 24 autosensing 10/100/1000 ports plus 2 SFP 100/1000 slots	
Physical characteristics	Dimensions	17.42(w) x 9.69(d) x 1.73(h) in (44.25 x 24.61 x 4.39 cm) (1U height)
	Weight	6 lb (2.72 kg)
Memory and processor	ARM Cortex-A9 @ 400 MHz, 128 MB SDRAM; Packet buffer size: 1.5 MB, 16 MB flash	
Performance	100 Mb Latency	< 7 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2 μ s (LIFO 64-byte packets)
	Throughput	up to 38.6 Mpps (64-byte packets)
	Switching capacity	52 Gbps
	MAC address table size	8000 entries
Reliability	MTBF (years)	80.00
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C)
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)
	Altitude	up to 9,842 ft (3 km)
	Acoustic	Power: 0 dB no fan
Electrical characteristics	Frequency	50/60 Hz
	AC Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	.5/.3 A
	Maximum power rating	22 W
	Idle power	16.9 W
	PoE power	
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if

Technical Specifications

		equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1
Emissions		FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A
Immunity	Generic	EN 55024, CISPR 24
	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management		Web browser
Notes		Use only supported genuine HPE mini-GBICs with your switch
Services		Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE OfficeConnect 1820 I/O ports and slots 24G PoE+ (185W) Switch (J9983A)

		12 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
		12 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
		2 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)
		Supports a maximum of 24 autosensing 10/100/1000 ports plus 2 SFP 100/1000 slots
Physical characteristics	Dimensions	17.42(w) x 9.69(d) x 1.73(h) in (44.25 x 24.61 x 4.39 cm) (1U height)
	Weight	7.3 lb (3.31 kg)
Memory and processor		ARM Cortex-A9 @ 400 MHz, 128 MB SDRAM; Packet buffer size: 1.5 MB, 16 MB flash
Performance	100 Mb Latency	< 7 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2 μ s (LIFO 64-byte packets)
	Throughput	up to 38.6 Mpps (64-byte packets)

Technical Specifications

	Switching capacity	52 Gbps
	MAC address table size	8000 entries
Reliability	MTBF (years)	64.52
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C)
	Nonoperating/Storage temperature	-40°F to 70°F (-40°C to 21.1°C)
	Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)
	Altitude	up to 9,842 ft (3 km)
	Acoustic	Power: 36 dB
Electrical characteristics	Frequency	50/60 Hz
	Voltage	100 - 127 / 200 - 240 VAC, rated (depending on power supply chosen)
	Current	2.6/1.3 A
	Maximum power rating	240 W
	Idle power	28.3 W
	PoE power	185 W PoE+
	Notes	<p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of an External Power Supply (EPS).</p>
	Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1
Emissions	FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A	
Immunity	Generic	EN 55024, CISPR 24
	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency	IEC 61000-4-8

Technical Specifications

	magnetic field	
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management	Web browser	
Notes	Use only supported genuine HPE mini-GBICs with your switch	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
<hr/>		
HPE OfficeConnect 1820 48G Switch (J9981A)	I/O ports and slots	
	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX)	
	Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 SFP ports	
	Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 SFP 100/1000 slots	
Physical characteristics	Dimensions	17.42(w) x 9.69(d) x 1.73(h) in (44.25 x 24.61 x 4.39 cm) (1U height)
	Weight	7.3 lb (3.31 kg)
Memory and processor	ARM Cortex-A9 @ 400 MHz, 128 MB SDRAM; Packet buffer size: 1.5 MB, 16 MB flash	
Performance	100 Mb Latency	< 7 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2 μ s (LIFO 64-byte packets)
	Throughput	up to 77.3 Mpps (64-byte packets)
	Switching capacity	104 Gbps
	MAC address table size	16000 entries
Reliability	MTBF (years)	61.73
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C)
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)
	Altitude	up to 9,842 ft (3 km)
	Acoustic	Power: 0 dB no fan
Electrical characteristics	Frequency	50/60 Hz

Technical Specifications

	Voltage	100 - 127 / 200 - 240 VAC, rated (depending on power supply chosen)
	Current	.8/ .5 A
	Maximum power rating	39 W
	Idle power	28.8 W
	PoE power	
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1
Emissions		FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A
Immunity	Generic	EN 55024, CISPR 24
	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management		Web browser
Notes		Use only supported genuine HPE mini-GBICs with your switch
Services		Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE OfficeConnect 1820 I/O ports and slots 48G PoE+ (370W) Switch (J9984A)

24 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

4 SFP 100/1000 Mbps ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u

Technical Specifications

	Type 100BASE-FX)
	Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 SFP 100/1000 slots
Physical characteristics	Dimensions 17.42(w) x 12.7(d) x 1.73(h) in (44.25 x 32.26 x 4.39 cm) (1U height)
	Weight 9.7 lb (4.4 kg)
Memory and processor	ARM Cortex-A9 @ 400 MHz, 128 MB SDRAM; Packet buffer size: 1.5 MB, 16 MB flash
Performance	100 Mb Latency < 7 μ s (LIFO 64-byte packets)
	1000 Mb Latency < 2 μ s (LIFO 64-byte packets)
	Throughput up to 77.3 Mpps (64-byte packets)
	Switching capacity 104 Gbps
	MAC address table size 16000 entries
Reliability	MTBF (years) 45.05
Environment	Operating temperature 32°F to 104°F (0°C to 40°C)
	Operating relative humidity 15% to 95% @ 104°F (40°C)
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 15% to 95% @ 140°F (60°C)
	Altitude up to 9,842 ft (3 km)
	Acoustic Power: 45 dB
Electrical characteristics	Frequency 50/60 Hz
	Voltage 100 - 127 / 200 - 240 VAC, rated (depending on power supply chosen)
	Current 5.1/2.6 A
	Maximum power rating 481 W
	Idle power 54.8 W
	PoE power 370 W PoE+
	Notes Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of an External Power Supply (EPS).

Technical Specifications

Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1	
Emissions	FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A	
Immunity	Generic	EN 55024, CISPR 24
	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management	Web browser	
Notes	Use only supported genuine HPE mini-GBICs with your switch	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Standards and protocols Denial of service protection

(Applies to all products in CPU DoS Protection series)

General protocols

IEEE 802.1D Spanning Tree Protocol
 IEEE 802.1p Priority
 IEEE 802.1Q VLANs
 IEEE 802.1W Rapid Spanning Tree Protocol
 IEEE 802.3ad Link Aggregation Control Protocol (LACP)
 IEEE 802.3x Flow Control
 RFC 1534 DHCP/BOOTP Interoperation
 RFC 2030 Simple Network Time Protocol (SNTP) v4

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

Accessories

HPE OfficeConnect 1820 Cables

Switch Series accessories

HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HP LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Mounting Kit

HPE X410 1U Universal 4-post Rackmount Kit	J9583A
--	--------

HPE OfficeConnect 1820 24G Switch (J9980A)

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X111 100M SFP LC FX Transceiver	J9054C

HPE OfficeConnect 1820 24G PoE+ (185W) Switch (J9983A)

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X111 100M SFP LC FX Transceiver	J9054C

HPE OfficeConnect 1820 48G Switch (J9981A)

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X111 100M SFP LC FX Transceiver	J9054C

HPE OfficeConnect 1820 48G PoE+ (370W) Switch (J9984A)

HPE X111 100M SFP LC FX Transceiver	J9054C
HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP LC to LC Multi-mode Cabling
OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable
 (AJ833A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zip cord graded index 50/125 μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP LC to LC Multi-mode Cabling
OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable
 (AJ834A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Accessory Product Details

Notes	<p>Maximum distance: 10Gbps Transfer Rate (Ethernet): 300m</p> <p>Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.</p> <ul style="list-style-type: none"> • Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um • Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm. • Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links. • CABLE: The cable is duplex zip cord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows. • BULK CABLE & CABLE ASSEMBLY CONFIGURATION: • Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic. • Jacket Color: Aqua for OM3 multimode per TIA 598 • Boot Color: White • Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters. • Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46. • Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg
Services	<p>Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.</p>

**HP LC to LC Multi-mode Cabling
OM3 2-Fiber 2.0m 1-
Pack Fiber Optic Cable
(AJ835A)**

Notes	<p>Cable type: 50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;</p> <p>Maximum distance: 10Gbps Transfer Rate (Ethernet): 300m</p> <p>Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.</p> <ul style="list-style-type: none"> • Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um • Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
--------------	---

Accessory Product Details

- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zip cord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP LC to LC Multi-mode Cabling OM3 2-Fiber 5.0m 1- Pack Fiber Optic Cable (AJ836A)

Cable type:

50/125 μm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zip cord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.

Accessory Product Details

- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP LC to LC Multi-mode Cabling OM3 2-Fiber 15.0m 1- Pack Fiber Optic Cable (AJ837A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 \pm 3.0 μm Cladding diameter: 125 \pm 2.0 μm Coating diameter: 245 \pm 10 μm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zip cord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-

Accessory Product Details

level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP LC to LC Multi-mode Cabling
OM3 2-Fiber 30.0m 1-
Pack Fiber Optic Cable
 (AJ838A)

Notes

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zip cord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP LC to LC Multi-mode Cabling
OM3 2-Fiber 50.0m 1-
Pack Fiber Optic Cable
 (AJ839A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

Accessory Product Details

Notes

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zip cord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m

Accessory Product Details

Services

- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m

Accessory Product Details

Services

- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m

Accessory Product Details

Services

- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE X410 1U Universal 4-post Rackmount Kit (J9583A) Notes

The rack mounting kit supports the 1U, full width switches in the following switch series and the power supply: V1810 Series, E2510 Series, E2520 Series, E2610 Series, E2810 Series, E2910 Series, E3500 Series, and the E620 Power Supply This universal rack mounting kit is design to fit the following racks: HPE 10K 10642, HPE 10K 10842, Panduit CN, Panduit CS, Wrightline Vantage S2, APC Netshelter 600mm, and APC Netshelter 800mm. It may well fit many other brands and models too.

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE X111 100M SFP LC FX Transceiver (J9054C) Ports Physical characteristics

1 LC 100BASE-FX port (IEEE 802.3u Type 100BASE-FX); Duplex: half or full
Dimensions: 2.7(d) x 0.54(w) x 0.48(h) in. (6.86 x 1.38 x 1.22 cm)
Weight: 0.06 lb. (0.03 kg)

Accessory Product Details

HPE X111 100M SFP LC FX **Environment**

Transceiver: An SFP format 100-megabit transceiver with LC connectors using FX technology.

Cabling

Operating temperature: 32°F to 158°F (0°C to 70°C)
 Operating relative humidity: 5% to 95%
 Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)
 Nonoperating/Storage relative humidity: 5% to 85%
 Altitude: up to 10,000 ft. (3 km)

Cable type:
 62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Maximum distance:
 • 2 km (full duplex) or 412 m (half duplex)

Notes

Transmitter wavelength: 1310nm
 Power consumption is 1.1 watt maximum.
 For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9054C 100-FX SFP-LC Transceiver" on the "ProCurve Mini-GBICs and SFPs" Manuals Web page.

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE X121 1G SFP LC SX Transceiver (J4858C)

A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.

Ports

1 LC 1000BASE-SX port; Duplex: full only

Physical characteristics

Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)
 Weight: 0.04 lb. (0.02 kg)
 Transceiver form factor: SFP

Environment

Operating temperature: 32°F to 158°F (0°C to 70°C)
 Operating relative humidity: 5% to 85%, noncondensing
 Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)
 Altitude: up to 10,000 ft. (3 km)

Electrical characteristics

Power consumption typical: 0.4 W
 Power consumption maximum: 0.7 W

Cabling

Type:
 • 62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;

Maximum distance:

- 2-220 m (62.5 μm core diameter, 160 MHz*km bandwidth)
- 2-275 m (62.5 μm core diameter, 200 MHz*km bandwidth)
- 2-500 m (50 μm core diameter, 400 MHz*km bandwidth)
- 2-550 m (50 μm core diameter, 500 MHz*km bandwidth)

Cable length: 2-550m

Fiber type: Multi Mode

Accessory Product Details

	Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.
HPE X121 1G SFP LC LX Transceiver (J4859C)	Ports	1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only
HPE X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.	Physical characteristics	Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm) Weight: 0.04 lb. (0.02 kg)
	Environment	Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 0% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C) Altitude: up to 10,000 ft. (3 km)
	Cabling	Type: <ul style="list-style-type: none"> Either single mode or multimode; 62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; <p>Maximum distance:</p> <ul style="list-style-type: none"> 2-550 m (multimode 62.5 μm core diameter, 500 MHz*km bandwidth) 2-550 m (multimode 50 μm core diameter, 400 MHz*km bandwidth) 2-550 m (multimode 50 μm core diameter, 500 MHz*km bandwidth) 2-10,000 m (single-mode fiber)
	Notes	A mode conditioning patch cord may be needed in some multimode fiber installations. Wavelength: 1310nm Power Consumption: < 500mW Typical
	Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.
HPE X121 1G SFP RJ45 T Transceiver (J8177C)	Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T); Duplex: full only
HPE X121 1G SFP RJ45 T Transceiver: An SFP format gigabit transceiver	Physical characteristics	Dimensions: 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm) Weight: 0.06 lb. (0.03 kg)
	Environment	Operating temperature: 32°F to 158°F (0°C to 70°C); with 100 LFM airflow over the SFP module)

Accessory Product Details

with RJ45 connectors using 1000BaseT technology.

Cabling

Operating relative humidity: 0% to 95% @ 75°F (25°C), noncondensing
 Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)
 Nonoperating/Storage relative humidity: 0% to 95% @ 77°F (25°C), noncondensing

Altitude: up to 10,000 ft. (3000 km)

Cable type:

1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;

Maximum distance:

- 100 m

Notes

Power consumption is nominally 1 watt.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J8177C 1000Base-T Mini-GBIC" on the "ProCurve Mini-GBICs and SFPs" Manuals Web page.

The J8177C Gigabit copper mini-GBIC is not supported on dual-personality ports.

The J8177C is capable of 100 Mb operation. This is supported on only the HPE ProCurve Switch 8200zl, 5400zl, and 6200yl Series using software version K.12.21 or later. Use the "auto-100" port setting to enable 100 Mb operation.

Important: The earlier J8177B does not support 100 Mb operation.

When used in the ProCurve Switch gl 20-Port 10/100/1000 Module (J4908A), the J8177C mini-GBIC can be installed in either the upper or lower mini-GBIC port, but will block access to the other port.

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

Date	Version History	Action	Description of Change:
06-May-2016	From Version 3 to 4	Changed	Document name changed to HPE OfficeConnect 1820 Switch Series. Overview, Features and Benefits, Technical Specifications updated.
22-Apr-2016	From Version 2 to 3	Changed	SKU descriptions updated on all document
01-Dec-2015	From Version 1 to 2	Changed	Overview, Features and Benefits and Technical Specifications updated

Summary of Changes



Sign up for updates

★ Rate this document

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

c04518995 - 15190 - Worldwide - V4 - 06-May-2016

