



LevelOne FEP-1601 netwerk-switch Fast Ethernet (10/100) Power over Ethernet (PoE) Grijs, Metallic

Merk : LevelOne

Artikelcode: FEP-1601

Productnaam : FEP-1601

16 x RJ-45, Fast Ethernet, PoE

LevelOne FEP-1601 netwerk-switch Fast Ethernet (10/100) Power over Ethernet (PoE) Grijs, Metallic:

Key Features:

- IEEE 802.3x datatransport-besturing beschermt tegen lost packets voor betrouwbare dataoverdracht
- 10/100Mbps-volledig/half duplex, automatische onderhandeling, automatische MDI/MDIX
- PoE aan/uit-regeling per poort met instelschakelaars
- Totale PoE-energiebudget: 250W, tot 30W per poort
- 19-inch metalen behuizing

LevelOne FEP-1601. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 4096 entries, Switchingcapaciteit: 3,2 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3x. Netstekker: DC-in ingang. Power over Ethernet (PoE). Rack-montage



Poorten & interfaces		Energie	
Aantal basis-switching RJ-45 Ethernet-poorten *	16	AC-ingangsspanning	100 - 240 V
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)	AC-ingangsfrequentie	50 - 60 Hz
Netstekker	DC-in ingang	Stroom	5 A
		Stroomspanning bescherming	Overstroom, Kortsluiting
Netwerk		Power over Ethernet (PoE)	
Netwerkstandaard *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) *	✓
10G support *	✗	Hoeveelheid Power over Ethernet (PoE) ports	16
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX	Vermogen per poort Power over Ethernet (PoE)	30 W
Full duplex	✓	Totaal Power over Ethernet (PoE)-budget	240 W
Datastroombeheer	✓	Eisen aan de omgeving	
Auto MDI/MDI-X	✓	Bedrijfstemperatuur (T-T)	0 - 45 °C
Auto-negotiation	✓	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	3,2 Gbit/s	Luchtvochtigheid bij opslag	10 - 90 procent
MAC-adrestabel *	4096 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	480 mm
Packet forwarding rate (100 Mbps)	148000 pps	Diepte	118 mm
Packet forwarding rate (10 Mbps)	14880 pps	Hoogte	44 mm
Design		Gewicht	2,2 kg
Rack-montage *	✓	Verpakking	
Kleur van het product	Grijs, Metallic	Meegeleverde kabels	AC
LED-indicatoren	Activiteit, Power over Ethernet (PoE), Stroom	Gebruikershandleiding	✓
Aan/uitschakelaar	✓	Breedte verpakking	222 mm
Land van herkomst	Taiwan	Diepte verpakking	146 mm
Certificering	FCC, CE, RoHS	Hoogte verpakking	78 mm
Prestatie		Gewicht verpakking	2,6 kg
Buffergrootte	160 KB	Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85176990	



4015867188002



4012700520838

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.